

My Literate GNU Emacs Config

Marius Peter

23 Jul, 2020 (Thu)

Contents

1	Introduction	5
2	TODO First-time setup	5
2.1	File system paths	5
3	Early setup	5
3.1	Garbage collection	5
3.2	Profiling — start	6
3.3	Emacs client	6
3.4	Custom file	6
3.5	Customization shortcuts	6
3.6	Backups	6
3.7	Initial and default frames	7
3.7.1	GNU/Linux	7
3.8	Secrets	7
4	Global key bindings	7
4.1	Keyboard navigation	7
4.1.1	Saving a file	8
4.1.2	Opening a file	8
4.1.3	Opening a recently visited file	8
4.1.4	Locating a file	8
4.1.5	Closing window and quitting Emacs	8
4.2	Mouse zoom	8
5	Packages	8
5.1	Meta	9
5.1.1	Package archives	9
5.1.2	TODO Convenient package update	9
5.1.3	use-package	9
5.2	org-mode	9
5.2.1	Basic customization	10
5.2.2	Invisible edits	10
5.2.3	Agenda	10
5.2.4	Timestamps	10
5.2.5	L ^A T _E X export	11
5.2.6	Export	12
5.3	TODO evil-mode	12
5.4	Spelling, completion, and snippets	12
5.4.1	flycheck	12
5.4.2	TODO flyspell	12
5.4.3	Insert template from keyword	12

5.4.4	Complete anything interactively	13
5.4.5	Delete all consecutive whitespaces	13
5.5	Utilities	13
5.5.1	Versioning of files	13
5.5.2	Navigate between projects	13
5.5.3	Display keyboard shortcuts on screen	13
5.5.4	Jump to symbol's definition	13
5.5.5	Graphical representation of file history	14
5.5.6	Auto-completion framework	14
5.6	File formats	14
5.6.1	csv and Excel	14
5.6.2	Interacting with PDFs	14
5.6.3	Accounting	14
5.6.4	Plotting & charting	15
5.7	Cosmetics	15
5.7.1	Start page	15
5.7.2	Mode line	15
5.7.3	TODO Sidebar	15
5.7.4	Better parentheses	15
5.7.5	Colored keywords for those colors	15
6	Editing preferences	15
6.1	Editor	16
6.1.1	Coding standards	16
6.1.2	Recent files	16
6.2	Frame	16
6.2.1	Clean up menus	16
6.2.2	Dividers	16
6.2.3	TODO Header & mode line	16
6.3	Window	17
6.4	Buffer	17
6.4.1	Column filling	17
6.5	Minibuffer	17
7	Themes	18
7.1	My light and dark themes	18
7.1.1	Colors	18
7.1.2	Cursors	19
7.1.3	Faces	19
7.2	TODO minimal	19
8	Late setup	19
8.1	Profiling — stop	20
8.2	Profiling — report	20

9 Conclusion	20
---------------------	-----------

List of Figures

List of Tables

1	Light and dark themes' colors	18
---	---	----

Abstract

GNU Emacs is most often used as a text editor. The utmost level of customization is afforded by enabling the user to rewrite *any* part of the source code and observe the editor's modified behaviour in real time. Since its inception in 1984, GNU Emacs has grown to be much more than a full-featured, high-productivity text editor—new *modes* have been written to interact with hundreds of file formats, including `.txt`, `.pdf`, `.jpg`, `.csv`, and `.zip` just to name a few. This configuration file itself was written in *Org mode*, a collection of functions enabling the harmonious mixing of code and comments in view of publication: this is the endgame of *literate programming*.

1 Introduction

The following sections were laid out very deliberately. When we start Emacs, Emacs Lisp source code blocks contained in this document are evaluated sequentially—our editing environment is constructed in real time as we execute the blocks in order. For instance, we only begin loading packages once we ensured `use-package` is working properly.

Customizing Emacs goes far, far beyond this document—feel free to experiment and discover.

- `C-h f` describe function
- `C-h v` describe variable
- `C-h k` describe key

These three commands will attempt to describe the element currently under our cursor, however you can start typing to search for another symbol.

2 TODO First-time setup

Spacemacs-like dialog for default settings.

2.1 File system paths

In this subsection, we tell Emacs about relevant paths to resources.

On my MS Windows machine, I add the path to Portable Git.¹

```
(when (string-equal system-type "windows-nt")  
  (add-to-list 'exec-path "C:/Users/marius.peter/PortableGit/bin/"))
```

3 Early setup

3.1 Garbage collection

First, we increase the RAM threshold beyond which the garbage collector is activated.

```
(setq gc-cons-threshold 100000000)
```

¹Download from <https://git-scm.com/download/win>

3.2 Profiling — start

We start the profiler now , and will interrupt it in Section 8.1. We will then present profiling report in Section 8.2.

```
; (profiler-start)
```

3.3 Emacs client

Makes opening emacs faster for following instances.

```
; (setq initial-buffer-choice (lambda () (get-buffer "*dashboard*")))
```

3.4 Custom file

Load settings created automatically by GNU Emacs Custom. (For example, any clickable option/toggle is saved here.) Useful for fooling around with M-x customize-group <package>.

user-emacs-directory

```
(setq custom-file (concat user-emacs-directory "init-custom.el"))  
(load custom-file)
```

3.5 Customization shortcuts

We begin by defining a user shortcut to this very file. We load this as early as possible, this facilitates debugging.

```
(defun my/find-literate-config ()  
  "Jump to this very file."  
  (interactive)  
  (find-file my/literate-config))  
  
(global-set-key (kbd "C-c c") 'my/find-literate-config)
```

Now, different shortcuts for other customization actions:

```
(global-set-key (kbd "C-c v") 'customize-variable)  
(global-set-key (kbd "C-c f") 'customize-face)
```

3.6 Backups

Backups are so important that they should be described right after the shortcut to this file.

```
(setq backup-directory-alist `(("*" . ,temporary-file-directory))  
auto-save-file-name-transforms `(("*" ,temporary-file-directory t))  
  backup-by-copying t ; Don't delink hardlinks
```

```
version-control t      ; Use version numbers on backups
delete-old-versions t  ; Automatically delete excess backups
kept-new-versions 20   ; how many of the newest versions to keep
kept-old-versions 5    ; and how many of the old
)
```

3.7 Initial and default frames

We set the dimensions of the initial and default frames.

```
(add-to-list 'default-frame-alist '(width . 100))
(add-to-list 'default-frame-alist '(height . 50))

(add-to-list 'initial-frame-alist '(width . 100))
(add-to-list 'initial-frame-alist '(height . 50))
```

3.7.1 GNU/Linux

These settings affect the first and subsequent frames spawned by Emacs in GNU/Linux. Frame transparency increases when focus is lost.

```
(when (and (display-graphic-p) (string-equal system-type "gnu/linux"))
  (set-frame-parameter (selected-frame) 'alpha '(90 . 50))
  (add-to-list 'default-frame-alist '(alpha . (90 . 50))))
```

3.8 Secrets

The code contained in the `secrets.org` file is loaded by Emacs, but not rendered in this PDF for the sake of privacy. It contains individually identifying information such as names and e-mail addresses, which are used to populate Org templates (Section 5.2).

You need to create this `secrets.org` file, as it is ignored by `git` by default.

```
(org-babel-load-file "~/emacs.d/blendoit/secrets.org")
```

4 Global key bindings

The following bindings strive to further enhance CUA² mode.

4.1 Keyboard navigation

```
(global-set-key (kbd "C-`") 'delete-other-windows)
```

²Common User Access.

4.1.1 Saving a file

```
(global-set-key (kbd "C-s") 'save-buffer)
```

4.1.2 Opening a file

```
(global-set-key (kbd "C-o") 'find-file)
```

4.1.3 Opening a recently visited file

```
(global-set-key (kbd "C-r") 'counsel-recentf)
```

4.1.4 Locating a file

```
(global-set-key (kbd "C-c l") 'counsel-locate)
```

4.1.5 Closing window and quitting Emacs

```
(defun my/delete-window-or-previous-buffer ()  
  "Delete window; if sole window, previous buffer."  
  (interactive)  
  (if (> (length (window-list)) 1)  
      (delete-window)  
      (previous-buffer)))
```

The following bindings lead to more natural exit behaviors.

```
(global-set-key (kbd "C-w") 'my/delete-window-or-previous-buffer)  
(global-set-key (kbd "C-q") 'save-buffers-kill-terminal)
```

4.2 Mouse zoom

The typical binding on both GNU/Linux and MS Windows is adequate here: `C-=` to zoom in, `C--` to zoom out.

It seems that starting with Emacs 27.1, Control + mousewheel works.

```
(global-set-key (kbd "C--") 'text-scale-decrease)  
(global-set-key (kbd "C-=") 'text-scale-increase)  
(global-set-key (kbd "C-+") 'text-scale-increase)
```

5 Packages

Packages are collections of `.el` files providing added functionality to Emacs.

5.1 Meta

How do we bootstrap packages? First, let's figure out:

1. Where we get our packages from
2. How we upgrade packages
3. How we ensure our required packages are installed

5.1.1 Package archives

List of package archives.

```
(require 'package)
(add-to-list 'package-archives '("melpa" . "https://melpa.org/packages/") t)
(add-to-list 'package-archives '("org" . "https://orgmode.org/elpa/") t)
(package-initialize)
```

5.1.2 TODO Convenient package update

One-function rollup of upgradeable package tagging, download and lazy install.

5.1.3 use-package

We ensure `use-package` is installed, as well as all packages described in this configuration file.

```
(unless (package-installed-p 'use-package)
  (package-refresh-contents)
  (package-install 'use-package)
  (eval-when-compile (require 'use-package)))
(setq use-package-always-ensure t)
(require 'use-package)
(require 'bind-key)
```

5.2 org-mode

Phew, I can finally introduce Org mode! I am so **excited**.

Org mode replaces a word processor, a presentation creator, and a spreadsheet editor. IMHO, the spreadsheet ability captures more than 80% use cases wherein one wishes to include a table in a text document destined for physical publication. (It is clear that Excel spreadsheets are *not* destined for physical publication—simply attempt to print an Excel spreadsheet with the default settings.) In my opinion, Org mode matches all *useful* features of the Microsoft Office suite 1-to-1.

What follows are customizations designed to make Org mode behave more like Microsoft Word. The end goal is, once again, to draw as many new users to Emacs as possible!

5.2.1 Basic customization

Org base directory is in user home on GNU/Linux, or in `AppData` in MS Windows.

```
(setq org-directory (concat user-emacs-directory "~/org"))
```

First, we hide markup symbols for **bold**, *italic*, underlined and ~~strikethrough~~ text, and ensure our document appears indented upon loading:³

For the time being, I will in fact display emphasis markers, because hiding them corrupts tables.

```
(setq org-hide-emphasis-markers nil)
(setq org-startup-indented t)
```

Then, we customize Org headings to emulate WYSIWYG⁴ behavior normally found in Word:

5.2.2 Invisible edits

```
(setq org-catch-invisible-edits t)
```

5.2.3 Agenda

The agenda displays a chronological list of headings across all agenda files for which the heading or body contain a matching `org-time-stamp`.⁵

```
(global-set-key (kbd "C-c a") 'org-agenda-list)

(defun my/find-diary-file ()
  "Load `org-agenda-diary-file'."
  (interactive)
  (find-file org-agenda-diary-file))

(global-set-key (kbd "C-c d") 'my/find-diary-file)
```

5.2.4 Timestamps

More literary timestamps are exported to L^AT_EX using the following custom format:

```
(setq org-time-stamp-custom-formats
  '("%d %b, %Y (%a)" . "%d %b, %Y (%a), at %H:%M"))
```

³It *appears* indented, but the underlying plaintext file does not contain tab characters!

⁴What You See Is What You Get (input and output are identical), as opposed to What You See Is What You Mean (the input contains instructions that can modify the output).

⁵An `org-time-stamp` can be inserted with `C-c .` (period)

5.2.5 L^AT_EX export

We'll be compiling our documents with LuaTeX. This will afford us some future-proofing, since it was designated as the successor to pdfTeX by the latter's creators.

First, we define the command executed when an Org file is exported to L^AT_EX. We'll use `latexmk`, the Perl script which automagically runs binaries related to L^AT_EX in the correct order and the right amount of times.

Options and why we need them:

-shell-escape required by minted to color source blocks

-pdflatex=lualatex we use lualatex to generate our PDF

-interaction=nonstopmode go as far as possible without prompting user for input

```
(setq org-latex-pdf-process
      '("latexmk -pdf -f \
-pdflatex=lualatex -shell-escape \
-interaction=nonstopmode -outdir=%o %f"))
```

We customize the format for org time stamps to make them pop in our exported L^AT_EX documents.

```
(setq org-latex-active-timestamp-format
      "\\texttt{%s}")
(setq org-latex-inactive-timestamp-format
      "\\texttt{%s}")
```

The following packages are loaded for every L^AT_EX export

```
(setq org-latex-packages-alist
      '(("AUTO" "polyglossia" t
         ("xelatex" "lualatex"))
        ("AUTO" "babel" t
         ("pdflatex"))
        ("AUTO" "booktabs" t
         ("pdflatex"))
        ("table,svgnames" "xcolor" t
         ("pdflatex"))))
```

Little bonus for GNU/Linux users: syntax highlighting for source code blocks in L^AT_EX exports.

```
(when (string-equal system-type "gnu/linux")
  (add-to-list 'org-latex-packages-alist '("AUTO" "minted" t
                                           ("pdflatex" "lualatex"))))

(setq org-latex-listings 'minted)
(setq org-latex-minted-options
      '(("style" "friendly") ())))
```

The following makes `TODO` items appear red and `CLOSED` items appear green in Org's L^AT_EX exports. Very stylish, much flair!

5.2.6 Export

This creates a shorter binding for the most common Org export: Org \rightarrow L^AT_EX \rightarrow PDF.

```
(defun my/org-quick-export ()
  "Org export to PDF and open.
  This basically reimplements `C-c C-e l o'."
  (interactive)
  (org-open-file (org-latex-export-to-pdf)))

(global-set-key (kbd "C-c e") 'my/org-quick-export)
```

5.3 TODO evil-mode

Forgive me, for I have sinned.

This is the 2nd most significant customization after `org-mode`. Enabling `evil-mode` completely changes editing keys. For more information on `vi` keybindings, visit <https://hea-www.harvard.edu/~fine/Tech/vi.html>.

```
(use-package evil)
; (setq evil-toggle-key "C-c d") ; devil...
; (evil-mode 1)
```

5.4 Spelling, completion, and snippets

The following customizations open the doors to vastly increased typing speed and accuracy.

5.4.1 flycheck

Syntax highlighting for Emacs.

```
(use-package flycheck)
(global-flycheck-mode)
```

5.4.2 TODO flyspell

```
(use-package flyspell)
(add-hook 'text-mode-hook 'flyspell-mode)
```

5.4.3 Insert template from keyword

Thanks to `yasnippet`, we can type certain keywords, press `TAB`, and this will automatically insert a text snippet. We may then navigate through the snippet by using `TAB` (next field) and `SHIFT-TAB` (previous field).

For instance: Typing `src` then pressing `TAB` will expand the keyword to the following text:

```
#+BEGIN_SRC emacs-lisp
```

```
#+END_SRC
```

We notice that `emacs-lisp` is highlighted—this is the first modifiable field.

```
(use-package yasnippet)
(yas-global-mode 1)
```

5.4.4 Complete anything interactively

```
; (add-hook 'after-init-hook 'global-company-mode)
```

5.4.5 Delete all consecutive whitespaces

```
(use-package hungry-delete
:init (hungry-delete-mode))
```

5.5 Utilities

5.5.1 Versioning of files

Wonderful Git porcelain for Emacs. Enables the administration of a Git repository in a pain-free way.

```
(use-package magit
:bind ("C-c g" . magit-status))
```

5.5.2 Navigate between projects

This enables us to better manage our `.git` projects.

```
(use-package projectile
:bind ("C-c p" . 'projectile-command-map)
:init (projectile-mode 1)
      (setq projectile-completion-system 'ivy))
```

5.5.3 Display keyboard shortcuts on screen

```
(use-package which-key
:init (which-key-mode))
```

5.5.4 Jump to symbol's definition

```
(use-package dumb-jump)
(add-hook 'xref-backend-functions #'dumb-jump-xref-activate)
```

5.5.5 Graphical representation of file history

```
(use-package undo-tree)
(global-undo-tree-mode)
```

5.5.6 Auto-completion framework

```
(use-package ivy
  :config (setq ivy-use-virtual-buffers t
                ivy-count-format "%d/%d "
                enable-recursive-minibuffers t))
(ivy-mode t)
```

1. Smartly suggesting interactive search matches
Wonderful counsellor!

```
(use-package counsel
  :bind ("M-x" . counsel-M-x)
  :config (counsel-mode t))

(global-set-key (kbd "C-f") 'counsel-grep-or-swiper)
```

2. Searching for items

```
(use-package swiper
  :bind (("C-f" . counsel-grep-or-swiper)))
```

5.6 File formats

5.6.1 csv and Excel

```
(use-package csv-mode)
```

5.6.2 Interacting with PDFs

Org mode shines particularly when exporting to PDF—Org files can reliably be shared and exported to PDF in a reproducible fashion.

```
(use-package pdf-tools)
;; (pdf-tools-install)
```

5.6.3 Accounting

```
(use-package ledger-mode
  :bind
  ("C-c r" . ledger-report)
  ("C-c C" . ledger-mode-clean-buffer))
```

5.6.4 Plotting & charting

```
(use-package gnuplot)
```

5.7 Cosmetics

5.7.1 Start page

We replace the standard welcome screen with our own.

```
(setq inhibit-startup-message t)
(use-package dashboard
  :config
  (dashboard-setup-startup-hook)
  (setq dashboard-startup-banner (concat user-emacs-directory "img/Safran_logo.s
  (setq dashboard-items '((recents . 5)
                          (projects . 5)))
  (setq dashboard-banner-logo-title "A modern professional text editor."))
```

5.7.2 Mode line

```
(use-package powerline)
```

5.7.3 TODO Sidebar

Get inspiration from `ibuffer-sidebar` and create a better sidebar.

```
;; (load-file)
```

5.7.4 Better parentheses

```
(use-package rainbow-delimiters
  :config (add-hook 'prog-mode-hook #'rainbow-delimiters-mode))
(electric-pair-mode)
(show-paren-mode 1)
```

5.7.5 Colored keywords for those colors

This highlights hexadecimal numbers which look like colors, in that same color.

```
(use-package rainbow-mode
  :init
  (add-hook 'prog-mode-hook 'rainbow-mode))
```

6 Editing preferences

These customizations enhance editor usability. They are not brought about

6.1 Editor

6.1.1 Coding standards

This is just a better default. Don't @ me.

```
(setq c-default-style "linux"
      c-basic-offset 4)
```

6.1.2 Recent files

The keybinding for opening a recently visited file is described in paragraph 4.1.3.

```
(recentf-mode 1)
(setq recentf-max-menu-items 25)
(setq recentf-max-saved-items 25)
(run-at-time nil (* 5 60) 'recentf-save-list)
```

6.2 Frame

6.2.1 Clean up menus

Originally, I wished to inhibit certain entries in the GUI menus. Not worth the effort at this time.

```
(menu-bar-mode -1)
(tool-bar-mode -1)
```

6.2.2 Dividers

This ensures users can resize windows using the GUI. It also creates a useful separation between the bottom of the frame and the echo area.

```
(menu-bar-bottom-and-right-window-divider)
```

6.2.3 TODO Header & mode line

Complete mode line rewrite. Might require new package.

Top of the buffer is more intuitive for buffer info, bottom is more intuitive for buffer action.

This is pretty much a gutted out powerline.

1. Header line

```
(defun my/header-line ()
  "My header line, yo."
  (setq header-line-format
        '("%e"
          (:eval
```



```
(let* ((active (powerline-selected-window-active))
      (face0 (if active 'powerline-active0 'powerline-inactive0))
      (lhs (list (powerline-row "%b" face0)))
      (rhs (list (if (buffer-modified-p)
                     (powerline-row "Modified" face0 'r)
                     "I did it!")
                 (powerline-fill face0 0))))
      (concat (powerline-render lhs)
              (powerline-fill face0
                              (powerline-width rhs))
              (powerline-render rhs))))))
```

```
(add-hook 'find-file-hook #'my/header-line)
```

2. Mode line

```
(defun my/mode-line ()
  "My header line, yo."
  (setq mode-line-format "%b"))

(add-hook 'find-file-hook #'my/mode-line)
```

6.3 Window

6.4 Buffer

Save cursor location in visited buffer after closing it or Emacs.

```
(save-place-mode 1)
```

6.4.1 Column filling

A line of text is considered “filled” when it reaches 79 characters in length.

```
(setq-default fill-column 79)
```

Automatically break lines longer than `fill-column`.

```
(add-hook 'org-mode-hook 'turn-on-auto-fill)
```

6.5 Minibuffer

We replace the longer `yes-or-no-p` questions with more convenient `y-or-n-p`.

```
(defalias 'yes-or-no-p 'y-or-n-p)
```

Disable minibuffer scroll bar.

```
(set-window-scroll-bars (minibuffer-window) nil nil)
```

7 Themes

Without a carefully designed theme, our editor could become unusable. Thus, we describe two themes that were developed purposefully and iteratively.

```
(setq custom-theme-directory (concat user-emacs-directory "themes/"))
(load-theme 'blendoit-light)
; (load-theme 'blendoit-dark)
```

7.1 My light and dark themes

A highly legible unambiguous and thoughtful theme.

7.1.1 Colors

The default face is a black foreground on a white background, this matches MS Word. We are striving for a simple, intuitive color scheme.

Most of the visual cues derived from color are identical in both light and dark themes (Table 1).

Table 1: Light and dark themes' colors.

Color	blendoit-light	blendoit-dark
Black	default text	default background
Lighter shades	lesser headers	<i>n/a</i>
White	default background	default text
Darker shades	<i>n/a</i>	lesser headers
Red	negative	<i>same</i>
Tomato	timestamp 'TODO'	<i>same</i>
Green	positive	<i>same</i>
ForestGreen	timestamp 'DONE'	<i>same</i>
Blue	interactable content; links	<i>same</i>
SteelBlue	anything Org mode; anchor color	<i>same</i>
DeepSkyBlue	highlight	<i>same</i>
DodgerBlue	isearch	<i>same</i>
Purple		

7.1.2 Cursors

In order to imitate other modern text editors, we resort to a blinking bar cursor. We choose red, the most captivating color, because the cursor is arguably the region on our screen:

1. most often looked at;
2. most often searched when lost.

In files containing only **fixed-pitch** fonts (i.e. files containing only code), the cursor becomes a high-visibility box.

In files containing a mix of **variable-pitch** and **fixed-pitch** fonts, the cursor is a more MS Word-like bar.

```
(setq-default cursor-type (quote bar))
```

7.1.3 Faces

- **default**: Hack
 - Legible, modern monospace font
 - Strict, sharp, uncompromising
- **fixed-pitch**: Hack
- **variable-pitch**: Liberation Sans
 - Libre alternative to Arial
- **org-block**: Hermit
 - Slightly wider than Hack
 - More opinionated shapes
 - Very legible parentheses

1. **variable-pitch-mode**

We use **variable-pitch-mode** for appropriate modes.

```
(add-hook 'org-mode-hook 'variable-pitch-mode)  
(add-hook 'info-mode-hook 'variable-pitch-mode)
```

2. **TODO** Default font size

Make default font size larger on displays of which the resolution is greater than **1920x1080**.

7.2 TODO minimal

8 Late setup

At this point, our editor is almost ready to run. Phew! All that's left to do is to interrupt our profiling activities, and smartly store the result of our profiling.

8.1 Profiling — stop

```
;; (profiler-stop)
```

8.2 Profiling — report

```
;; (profiler-report)
```

9 Conclusion

In this configuration file, we described a series of customization steps taken to make Emacs more palatable to modern IDE users.