

My literate GNU Emacs config

Marius Peter

23 Jul, 2020 (Thu)

Contents

1	TODO First-time setup	4
2	Early setup	4
2.1	Garbage collection	4
2.2	Emacs client	4
2.3	Refresh configuration	4
2.4	Custom file	4
2.5	Profiling — start	4
2.6	Customization shortcuts	5
2.7	Backups	5
2.8	Secrets	5
2.9	File system paths	5
3	Global key bindings	6
3.1	Navigation	6
3.1.1	Graphical file open	6
3.1.2	Exit behaviours	6
3.2	Mouse zoom	6
4	Packages	7
4.1	Package archives	7
4.2	use-package	7
4.3	TODO Convenient package update	7
4.4	ivy	7
4.4.1	counsel	7
4.4.2	swiper	8
4.5	evil-mode	8
4.6	org-mode	8
4.6.1	Basic customization	8
4.6.2	Invisible edits	8
4.6.3	Agenda	9
4.6.4	Timestamps	9
4.6.5	ℒ _{TEX} export	9
4.6.6	Publish	9
4.6.7	Export	10
4.7	undo-tree	11
4.8	dumb-jump	11
4.9	gnuplot	11
4.10	Ledger	11
4.11	ibuffer-sidebar	11
4.12	TODO Sidebar	11
4.13	which-key	11
4.14	company	12

4.15 flycheck	12
4.16 csv-mode	12
4.17 json-mode	12
4.18 magit	12
4.19 pdf-tools	12
4.20 dashboard	12
4.21 rainbow-mode	13
4.22 projectile	13
4.23 all-the-icons	13
4.24 Better parentheses	13
5 Cosmetics	13
5.1 Cursors	13
5.1.1 Default cursor	14
5.2 Faces	14
5.2.1 mixed-pitch	14
5.3 Initial frame	14
5.4 Theme	15
5.4.1 blendoit-light	15
5.4.2 blendoit-dark	15
6 Editing preferences	15
6.1 Clean up menus	15
6.2 Coding standards	16
6.3 Dividers	16
6.4 Tabs	16
6.5 auto-fill	16
6.6 Recent files	16
6.7 pop-up-frames	16
7 Late setup	16
7.1 Profiling — stop	16
7.2 Profiling — report	16
8 Conclusion	16

List of Figures

List of Tables

Abstract

GNU Emacs is most often used as a text editor. The utmost level of customisation is afforded by enabling the user to rewrite *any* part of the source code and observe the editor's modified behaviour in real time. Since its inception in 1984, GNU Emacs has grown to be much more than a full-featured, high-productivity text editor—new *modes* have been written to interact with hundreds of file formats, including .txt, .pdf, .jpg, .csv, and .zip just to name a few. This configuration file itself was written in *Org mode*, a collection of functions enabling the harmonious mixing of code and comments in view of publication: this is the endgame of *literate programming*.

1 TODO First-time setup

Spacemacs-like dialog for default settings.

```
;; Prompt enterprise or personal install. Create file in .emacs.d/ on Linux,  
;; AppData/ on Windows. Ask user for details and preferred bindings.
```

2 Early setup

2.1 Garbage collection

First, we increase the RAM threshold beyond which the garbage collector is activated.

```
(setq gc-cons-threshold 100000000)
```

2.2 Emacs client

Makes opening emacs faster for following instances.

```
; (setq initial-buffer-choice (lambda () (get-buffer "*dashboard*")))
```

2.3 Refresh configuration

Add an after-save-hook that tangles and loads this literary configuration.

2.4 Custom file

Load settings created automatically by GNU Emacs Custom. (For example, any clickable option/toggle is saved here.) Useful for fooling around with M-x customize-group <package>.

```
(setq custom-file "~/emacs.d/init-custom.el")  
(load custom-file)
```

2.5 Profiling — start

We start the profiler now , and will interrupt it in section 7.1. We will then present profiling report in section 7.2.

```
; (profiler-start)
```

2.6 Customization shortcuts

We begin by defining a user shortcut to this very file:

```
(defun find-init-blendoit ()  
  "Jump to this very file."  
  (interactive)  
  (find-file "~/emacs.d/blendoit/blendoit-init.org"))  
  
(global-set-key (kbd "C-c c") 'find-init-blendoit)
```

Now, different shortcuts for other customization actions:

```
(global-set-key (kbd "C-c v") 'customize-variable)  
(global-set-key (kbd "C-c f") 'customize-face)
```

2.7 Backups

Backups are so important that they should be described right after the shortcut to this file.

```
(setq backup-directory-alist '((".*" . ,temporary-file-directory))  
auto-save-file-name-transforms '((".*" ,temporary-file-directory t))  
  backup-by-copying t      ; Don't delink hardlinks  
  version-control t        ; Use version numbers on backups  
  delete-old-versions t    ; Automatically delete excess backups  
  kept-new-versions 20     ; how many of the newest versions to keep  
  kept-old-versions 5      ; and how many of the old  
)
```

2.8 Secrets

```
(setq user-full-name "Marius Peter"  
      user-mail-address "blendoit@gmail.com")  
  
(setq user-full-name "Marius Peter"  
      user-mail-address "blendoit@gmail.com")
```

2.9 File system paths

In this subsection, we tell Emacs about relevant paths to resources.

On my MS Windows machine, I add the path to Portable Git.¹

```
(if (string-equal system-type "windows-nt")  
    (add-to-list 'exec-path "C:/Users/marius.peter/PortableGit/bin/"))
```

¹Download from <https://git-scm.com/download/win>

3 Global key bindings

The following bindings strive to further enhance CUA² mode.

3.1 Navigation

```
(global-set-key (kbd "C-'"') 'delete-other-windows)
(global-set-key (kbd "C-s") 'save-buffer)
(global-set-key (kbd "C-b") 'ibuffer-sidebar-toggle-sidebar)
(global-set-key (kbd "C-r") 'counsel-recentf)
; (global-set-key (kbd "C-n") 'make-frame) ; 7aram!
```

3.1.1 Graphical file open

Open file with C-o.

```
(global-set-key (kbd "C-o") 'menu-find-file-existing)
```

We trick Emacs into opening file dialog with C-o instead of prompting for a file in minibuffer.

```
(defadvice find-file-read-args (around find-file-read-args-always-use-dialog-box act)
  "Simulate invoking menu item as if by the mouse; see 'use-dialog-box'."
  (let ((last-nonmenu-event nil))
    ad-do-it))
```

3.1.2 Exit behaviours

The following bindings lead to more natural exit behaviors.

```
(defun delete-window-or-previous-buffer ()
  "Delete window; if sole window, previous buffer."
  (interactive)
  (if (> (length (window-list)) 2)
      (delete-window)
      (previous-buffer)))

(global-set-key (kbd "C-w") 'delete-window-or-previous-buffer)
(global-set-key (kbd "C-q") 'save-buffers-kill-terminal)
```

3.2 Mouse zoom

The typical binding on both GNU/Linux and MS Windows is adequate here: C-= to zoom in, C-- to zoom out.

```
(global-set-key (kbd "C--") 'text-scale-decrease)
(global-set-key (kbd "C-=") 'text-scale-increase)
(global-set-key (kbd "C-+") 'text-scale-increase)
```

²Common User Access.

4 Packages

Packages are collections of .el files providing added functionality to Emacs.

4.1 Package archives

List of package archives.

```
(require 'package)
(add-to-list 'package-archives '("melpa" . "https://melpa.org/packages/") t)
(add-to-list 'package-archives '("org" . "https://orgmode.org/elpa/") t)
(package-initialize)
```

4.2 use-package

Ensure use-package is installed, as well as all packages described in this configuration file.

```
(unless (package-installed-p 'use-package)
  (package-refresh-contents)
  (package-install 'use-package)
  (eval-when-compile (require 'use-package)))
(setq use-package-always-ensure t)
```

4.3 TODO Convenient package update

One-function rollup of upgradeable package tagging, download and lazy install.

4.4 ivy

Auto completion.

```
(use-package ivy
  :config
  (setq ivy-use-virtual-buffers t
        ivy-count-format "%d/%d "
        enable-recursive-minibuffers t))
(ivy-mode t)
```

4.4.1 counsel

Wonderful counsellor!

```
(use-package counsel
  :bind ("M-x" . counsel-M-x)
  :config (counsel-mode t))

(global-set-key (kbd "C-f") 'counsel-grep-or-swiper)
```

4.4.2 swiper

```
(use-package swiper
  :bind (("C-f" . counsel-grep-or-swiper)))
```

4.5 evil-mode

Forgive me, for I have sinned.

```
(use-package evil)
;; (evil-mode 1)
```

4.6 org-mode

Phew, I can finally introduce Org mode! I am so **excited**.

Org mode replaces a word processor, a presentation creator, and a spreadsheet editor. IMHO, the spreadsheet ability captures more than 80% use cases wherein one wishes to include a table in a text document destined for physical publication. (It is clear that Excel spreadsheets are *not* destined for physical publication—simply attempt to print an Excel spreadsheet with the default settings.) In my opinion, Org mode matches all *useful* features of the Microsoft Office suite 1-to-1.

What follows are customizations designed to make Org mode behave more like Microsoft Word. The end goal is, once again, to draw as many new users to Emacs as possible!

4.6.1 Basic customization

Org base directory is in user home on GNU/Linux, or in AppData in MS Windows.

```
(setq org-directory "~/org")
```

First, we hide markup symbols for **bold**, *italic*, underlined and ~~strikethrough~~ text, and ensure our document appears indented upon loading.³

For the time being, I will in fact display emphasis markers, because hiding them corrupts tables.

```
(setq org-hide-emphasis-markers t)
(setq org-startup-indented t)
```

Then, we customize Org headings to emulate WYSIWYG⁴ behavior normally found in Word:

4.6.2 Invisible edits

```
(setq org-catch-invisible-edits t)
```

³It *appears* indented, but the underlying plaintext file does not contain tab characters!

⁴What You See Is What You Get (input and output are identical), as opposed to What You See Is What You Mean (the input contains instructions that can modify the output).

4.6.3 Agenda

The agenda displays a chronological list of headings across all agenda files for which the heading or body contain a matching `org-time-stamp`.⁵

```
(global-set-key (kbd "C-c a") 'org-agenda-list)
```

4.6.4 Timestamps

More literary timestamps are exported to \LaTeX using the following custom format:

```
(setq org-time-stamp-custom-formats
      '("%d %b, %Y (%a)" . "%d %b, %Y (%a), at %H:%M"))
```

4.6.5 \LaTeX export

The following makes CLOSED items appear green in \LaTeX . Very stylish, much flair!

```
(setq org-latex-inactive-timestamp-format
      "\\textcolor{ForestGreen!60}{\\textit{%s}}")
```

4.6.6 Publish

In the following *alist* (association list), we describe the projects publishable via `org-publish`. We separate the publishing of `.org` files and attachments, because an online tutorial recommended we do so.

```
(require 'ox-publish)
(setq org-publish-project-alist
      '(
        ("Safran-VIP-html"
         :base-directory "~/org/WORK/Safran/programs/B787/VIP/doc/org/"
         :base-extension "org"
         :publishing-directory "~/org/WORK/Safran/programs/B787/VIP/doc/wiki/"
         :recursive t
         :publishing-function org-html-publish-to-html
         :auto-preamble t
         :auto-sitemap t
         :sitemap-title "" )

        ("Safran-VIP-static"
         :base-directory "~/org/WORK/Safran/programs/B787/VIP/doc/org/"
         :base-extension "css\\|js\\|png\\|jpg\\|gif\\|pdf\\|mp3\\|mp4\\|ogg\\|swf"
         :publishing-directory "~/org/WORK/Safran/programs/B787/VIP/doc/wiki/"
         :recursive t
```

⁵An `org-time-stamp` can be inserted with `C-c .` (period)

```

:publishing-function org-publish-attachment )

("Safran-VIP-all"
 :components ("Safran-VIP-html" "Safran-VIP-static"))

("Safran-MA700-html"
 :base-directory "~/org/WORK/Safran/programs/MA700/doc/org/"
 :base-extension "org"
 :publishing-directory "~/org/WORK/Safran/programs/MA700/doc/wiki/"
 :recursive t
 :publishing-function org-html-publish-to-html
 :auto-preamble t
 :auto-sitemap t
 :sitemap-title "" )

("Safran-MA700-static"
 :base-directory "~/org/WORK/Safran/programs/MA700/doc/org/"
 :base-extension "css\\|js\\|png\\|jpg\\|gif\\|pdf\\|mp3\\|mp4\\|ogg\\|swf"
 :publishing-directory "~/org/WORK/Safran/programs/MA700/doc/wiki/"
 :recursive t
 :publishing-function org-publish-attachment )

("Safran-MA700-all"
 :components ("Safran-MA700-html" "Safran-MA700-static"))))

(add-to-list 'org-latex-packages-alist '("table" "xcolor"
  t ("pdflatex"))))
(add-to-list 'org-latex-packages-alist '("AUTO" "babel"
  t ("pdflatex"))))
(add-to-list 'org-latex-packages-alist '("AUTO" "polyglossia"
  t ("xelatex" "lualatex"))))

```

4.6.7 Export

This creates a shorter binding for the most common Org export: Org \rightarrow \LaTeX \rightarrow PDF.

```

(defun blendoit-org-quick-export ()
  "Org export to PDF and open.
  This basically reimplements 'C-c C-e l o'."
  (interactive)
  (org-open-file (org-latex-export-to-pdf)))

(global-set-key (kbd "C-c e") 'blendoit-org-quick-export)

```

4.7 undo-tree

```
(global-undo-tree-mode)
```

4.8 dumb-jump

```
(use-package dumb-jump)
(add-hook 'xref-backend-functions #'dumb-jump-xref-activate)
```

4.9 gnuplot

```
(use-package gnuplot)
```

4.10 Ledger

```
(use-package ledger-mode
  :bind
  ("C-c r" . ledger-report)
  ("C-c C" . ledger-mode-clean-buffer))
```

4.11 ibuffer-sidebar

```
;; (use-package ibuffer-sidebar)
;; (ibuffer-sidebar-show-sidebar)

;      :bind ("mouse-1" . ibuffer-mouse-visit-buffer)
;      :bind ("mouse-3" . ibuffer-mouse-toggle-mark))

;      (add-hook 'ibuffer-sidebar-mode-hook
;      (lambda ()
;      (local-unset-key (quote mouse-1))
;      (local-unset-key (quote mouse-2))
;      (local-set-key (quote mouse-1) (quote ibuffer-mouse-visit-buffer))
;      (local-set-key (quote mouse-2) (quote ibuffer-mouse-toggle-mark)))))
```

4.12 TODO Sidebar

Get inspiration from `ibuffer-sidebar` and create a better sidebar.

```
;; (load-file)
```

4.13 which-key

```
(use-package which-key
  :init
  (which-key-mode))
```

```
;; :config
;; (setq which-key-idle-delay 1000)
;; (setq which-key-idle-secondary-delay 0.05)
;; (setq which-key-show-early-on-C-h t)
)
```

4.14 company

```
; (add-hook 'after-init-hook 'global-company-mode)
```

4.15 flycheck

```
(use-package flycheck
  :init (global-flycheck-mode))
```

4.16 csv-mode

```
(use-package csv-mode)
```

4.17 json-mode

Oí, Jason!

```
(use-package json-mode)
```

4.18 magit

```
(use-package magit
  :bind ("C-c g" . magit-status))
```

4.19 pdf-tools

```
(use-package pdf-tools)
;; (pdf-tools-install)
```

4.20 dashboard

We replace the standard welcome screen with our own.

```
(setq inhibit-startup-message t)
(use-package dashboard
  :config
  (dashboard-setup-startup-hook)
  (setq dashboard-startup-banner "~/ .emacs.d/blendoit/img/Safran_logo.svg")
  (setq dashboard-items '((recents . 5)
    (projects . 5)))
  (setq dashboard-banner-logo-title "A modern professional text editor."))
```

4.21 rainbow-mode

This highlights hexadecimal numbers which look like colors, in that same color.

```
(use-package rainbow-mode
  :ensure t
  :init
  (add-hook 'prog-mode-hook 'rainbow-mode))
```

4.22 projectile

This enables us to better manage our .git projects.

```
(use-package projectile
  :bind ("C-c p" . 'projectile-command-map)
  :init (projectile-mode 1)
  (setq projectile-completion-system 'ivy))
```

4.23 all-the-icons

```
(use-package all-the-icons)
```

4.24 Better parentheses

```
(show-paren-mode 1)
```

```
(use-package smartparens
  :config
  (add-hook 'prog-mode-hook #'smartparens-mode))
```

```
(use-package rainbow-delimiters
  :config
  (add-hook 'prog-mode-hook #'rainbow-delimiters-mode))
```

5 Cosmetics

5.1 Cursors

In order to imitate other modern text editors, we resort to a blinking bar cursor. We choose red, the most captivating color, because the cursor is arguably the region on our screen:

1. most often looked at;
2. most often searched when lost.

5.1.1 Default cursor

In files containing only fixed-pitch fonts (i.e. files containing only code), the cursor becomes a high-visibility box.

In files containing a mix of variable-pitch and fixed-pitch fonts, the cursor is a more MS Word-like bar.

```
(setq-default cursor-type (quote box))
(setq-default mixed-pitch-variable-pitch-cursor (quote bar))
```

5.2 Faces

- default: Hack
 - Legible, modern monospace font
 - Strict, sharp, uncompromising
- fixed-pitch: Hack
- variable-pitch: Liberation Sans
 - Libre alternative to Arial
- org-block: Hermit
 - Slightly wider than Hack
 - More opinionated shapes
 - Very legible parentheses

5.2.1 mixed-pitch

Fixed-pitch and variable-pitch faces will be used intelligently in all hooked modes.

mixed-pitch is good at automatically determining which faces should be monospaced and proportional; I prefer to define each face in my custom theme.

```
;; (use-package mixed-pitch
;;   :hook ((org-mode . mixed-pitch-mode)
;;          (Info-mode . mixed-pitch-mode)))

(add-hook 'text-mode-hook 'variable-pitch-mode)
(add-hook 'info-mode-hook 'variable-pitch-mode)
```

5.3 Initial frame

These settings affect the first and subsequent frames spawned by Emacs in GNU/Linux. Frame transparency increases when focus is lost.

```
; (if (and (display-graphic-p) (string-equal system-type "gnu/linux"))
;   ((set-frame-parameter (selected-frame) 'alpha '(85 . 50))
;   (add-to-list 'default-frame-alist '(alpha . (85 . 50)))))
```

5.4 Theme

My custom themes.

```
(setq custom-theme-directory "~/emacs.d/blendoit/themes/")  
; (load-theme 'blendoit-light)  
(load-theme 'blendoit-dark)
```

5.4.1 blendoit-light

A highly legible and unambiguous theme.

The default face is a black foreground on a white background, this matches with MS Word.

Red TODO; cursor; negative; danger

Green DONE; positive

Blue document structure

Purple org-mode elements

5.4.2 blendoit-dark

Same principle

6 Editing preferences

These customizations enhance editor usability.

A line of text is considered ‘filled’ when it reaches 79 characters in length.

```
(setq-default fill-column 79)
```

We replace the longer yes-or-no-p questions with more convenient y-or-n-p.

```
(defalias 'yes-or-no-p 'y-or-n-p)
```

Disable minibuffer scroll bar.

```
(set-window-scroll-bars (minibuffer-window) nil nil)  
; (set-window-scroll-bars (ibuffer-sidebar-window) nil nil)
```

6.1 Clean up menus

Originally, I wished to inhibit certain entries in the GUI menus. Not worth the effort at this time.

```
(setq menu-bar-mode t)
```

6.2 Coding standards

This is just a better default. Don't @ me.

```
(setq c-default-style "linux"
      c-basic-offset 4)
```

6.3 Dividers

This ensures users can resize windows using the GUI.

```
(menu-bar-bottom-and-right-window-divider)
```

6.4 Tabs

6.5 auto-fill

Automatically break lines longer than `fill-column`.

```
(add-hook 'org-mode-hook 'turn-on-auto-fill)
```

6.6 Recent files

```
(recentf-mode 1)
(setq recentf-max-menu-items 25)
(setq recentf-max-saved-items 25)
(run-at-time nil (* 5 60) 'recentf-save-list)
```

6.7 pop-up-frames

```
; (setq pop-up-frames (quote graphic-only))
```

7 Late setup

7.1 Profiling — stop

```
;; (profiler-stop)
```

7.2 Profiling — report

```
;; (profiler-report)
```

8 Conclusion

In this configuration file, we described a series of customization steps taken to make Emacs more palatable to modern IDE users.