

Smart Documents

Marius Peter

<2021-02-09 Tue>

Contents

1	Introduction	6
1.1	TODO User details	6
1.2	File system paths	7
2	Early setup	7
2.1	The first file to load	7
2.2	The second file to load	7
2.3	Profiling—start	8
2.4	Jumping to this file	8
2.5	Meta-files	8
2.5.1	Recently visited files	8
2.5.2	Projects’ bookmarks	8
2.5.3	Location in previously visited file	9
2.5.4	Custom file	9
2.6	Backups	9
2.7	Initial and default frames	9
2.8	Secrets	10
3	Keyboard shortcuts	10
3.1	CUA mode	10
3.2	Files	10
3.2.1	Save a file	10
3.2.2	Open a file	10
3.2.3	List open files	10
3.2.4	Open this very file	10
3.2.5	Open a recently visited file	11
3.2.6	Locate a file	11
3.2.7	Open the agenda	11
3.2.8	Open the diary	11
3.2.9	Open Org mode document properties	11
3.3	Windows	11
3.3.1	Close window and quit	11
3.4	Frame	11
3.4.1	Make new frame	11
3.4.2	Make only frame	11
3.4.3	Delete frame or kill Emacs	11
3.4.4	Remap C-z when using a graphical interface	12
3.5	Text display	12
3.5.1	Zoom	12
3.6	TODO Navigation	12
3.6.1	Move down one line	13
3.6.2	Move up one line	13

3.6.3	Move left one character	13
3.6.4	Move right one character	13
3.7	Accessing customization	13
3.7.1	Customize a variable	13
3.7.2	Customize a face	13
3.8	One-click workflows	13
3.8.1	Export to PDF	13
3.8.2	Indent buffer	14
3.8.3	TODO Beautify Org mode buffer	14
4	Packages	14
4.1	Meta	14
4.1.1	Package archives	14
4.1.2	TODO Convenient package update	15
4.1.3	use-package	15
4.2	evil-mode	15
4.3	Spelling, completion, and snippets	15
4.3.1	Syntax checking	15
4.3.2	Spelling	15
4.3.3	Completion	16
4.3.4	Insert template from keyword	16
4.3.5	Delete all consecutive whitespaces	16
4.4	Utilities	16
4.4.1	Versioning of files	16
4.4.2	Navigate between projects	16
4.4.3	Display keyboard shortcuts on screen	17
4.4.4	Jump to symbol's definition	17
4.4.5	Graphical representation of file history	17
4.4.6	Auto-completion framework	17
4.4.7	Web browsing	17
4.4.8	IRC	18
4.4.9	TODO Telegram	18
4.5	Coding languages	19
4.5.1	TODO Emacs Lisp	19
4.5.2	Python	19
4.6	File formats	19
4.6.1	csv and Excel	19
4.6.2	Interacting with PDFs	19
4.6.3	Accounting	19
4.6.4	Plotting & charting	20
4.7	Cosmetics	20
4.7.1	Start page	20
4.7.2	Better parentheses	20
4.7.3	Highlight <i>color</i> keywords in that color	20

4.7.4	Minor modes in mode line	20
4.7.5	Emojis	20
5	org-mode	21
5.1	Introduction	21
5.2	Basic customization	21
5.2.1	Base folder	21
5.2.2	Prevent/warn on invisible edits	22
5.3	Org cosmetics	22
5.3.1	Pretty L ^A T _E X symbols	22
5.3.2	Dynamic numbering of headlines	22
5.3.3	Document properties	23
5.3.4	Timestamps	23
5.3.5	Sequence of TODOs	23
5.4	Programming a Smart Documents	24
5.5	Agenda	24
5.6	L ^A T _E X export	24
5.6.1	Exporting timestamps	25
5.6.2	L ^A T _E X packages	25
5.6.3	Colored source blocks in PDF export	26
5.6.4	Cleaning directory after export	26
5.6.5	Chronological diary entries	26
5.6.6	Extra L ^A T _E X class	26
5.6.7	Table of contents	27
5.6.8	AUCTEX	27
5.6.9	Groff export	27
5.7	TODO Org links	27
6	One-click workflows	28
6.1	TODO Export to PDF	28
6.1.1	From Org mode	28
6.1.2	From a Ledger report	28
6.1.3	From Nroff mode	29
6.1.4	Quick export	29
6.2	Beautify buffer	29
6.3	Smart window quitting	30
6.4	Smart frame quitting	30
7	Editing preferences	30
7.1	Editor	30
7.1.1	Coding standards	30
7.1.2	Recent files	30
7.1.3	Reload changed files silently	30
7.2	Frame	31

7.2.1	Header & mode lines	31
7.3	Window	33
7.4	Buffer	33
7.4.1	Save cursor location	33
7.4.2	Column filling	34
7.5	Text	34
7.5.1	Beautiful symbols	34
7.5.2	Org mode sugar	34
7.5.3	Electric modes	35
7.6	Minibuffer	35
8	Themes	35
8.1	My light and dark themes	35
8.1.1	Colors	36
8.1.2	Cursors	36
8.1.3	TODO Fonts	37
8.2	TODO <i>Wealthy</i> document theme	38
8.2.1	Symbol substitution	39
8.3	TODO <i>minimal</i>	39
9	Late setup	39
9.1	Profiling—stop	39
9.2	Profiling—report	40
10	Conclusion	40

List of Figures

1	Claude Garamont, an icon of font design	39
---	---	----

List of Tables

1	Navigation keybindings	12
2	Light and dark themes' colors	36

Abstract

The idea of *Smart Documents* came to me as I was reflecting on how to improve the document creation process in my workplace. The GNU Emacs editor had captured my imagination, and I wanted to create an accessible and highly productive text editor to benefit my organization. In this paper, I'll lay out my vision for the *Smart Document*, a file containing both text destined to the reader, and code describing how to update, validate, and present this text; then, I'll weave my personal GNU Emacs customizations with a tutorial. This paper is a *Smart Document* itself!

1 Introduction

The following sections were laid out very deliberately. When we start Emacs, the source code blocks contained in this document are evaluated sequentially — our editing environment is constructed in real time as we execute the blocks in order. For instance, we only begin loading packages once we ensured use-package is working properly.¹

Customizing Emacs goes far, far beyond rewriting sections of this document — feel free to experiment and discover. Here are three commands that will help you understand all the symbols in this file, if you are browsing this paper within Emacs itself:

C-h f describe function

C-h v describe variable

C-h k describe key

You can press f1 at any time to access Emacs built-in help.

1.1 TODO User details

One advantage of working with *Smart Documents* is that they can automatically be populated with our details in the header, footer, or other appropriate element.

```
(setq user-full-name "Marius Peter")

(defun my/user-details-get ()
  "Get user details."
  (interactive)
  (setq user-full-name (read-string "Enter full user name:"))
  (setq user-mail-address (read-string "Enter user e-mail
↪ address:"))
  (message "Successfully captured user details."))
```

¹For more information on the detailed steps Emacs takes upon starting, refer to https://www.gnu.org/software/emacs/manual/html_node/elisp/Startup-Summary.html.

```
(defun my/tokenize-user-details ()
  "Tokenize user details."

  (cons 'user-full-name user-full-name))

(unless (file-exists-p (concat user-emacs-directory
                              "meta/user-details"))
  (setq user-details '(user-full-name
                      user-mail-address))
  (append-to-file "Foobar\n" nil "~/.emacs.d/meta/foobar"))
```

1.2 File system paths

In this subsection, we tell Emacs about relevant paths to resources.

On my MS Windows machine, I add the path to Portable Git.²

```
(when (string-equal system-type "windows-nt")
  (add-to-list 'exec-path
    ↪ "C:/Users/marius.peter/PortableGit/bin/"))
```

2 Early setup

2.1 The first file to load

The contents of this Section was automatically moved to ~/.emacs.d/init.el. Use 'sd-pack-section' to copy the contents back into this section.

This is the very first user-editable file loaded by Emacs.³ In it, we disable GUI elements that would otherwise be loaded and displayed once Emacs is ready to accept user input.

It can be found here: early-init.el

2.2 The second file to load

Traditionally, file ~/.emacs is used as the init file, although Emacs also looks at the following locations:

- ~/.emacs.el
- ~/.emacs.d/init.el
- ~/.config/emacs/init.el.

From the GNU website⁴

²Download from <https://git-scm.com/download/win>

³This feature became available in version 27.1.

⁴https://www.gnu.org/software/emacs/manual/html_node/emacs/Init-File.html

This file can be found here: `init.el`

If no file is found, Emacs then loads in its purely vanilla state.

2.3 Profiling — start

We start the profiler now, and will interrupt it in Section 9.1. We will then present profiling report in Section 9.2.

```
(profiler-start)
```

2.4 Jumping to this file

We begin by defining a function to open this very file.

```
(defun my/find-literate-config ()  
  "Jump to this very file."  
  (interactive)  
  (find-file my/literate-config))
```

2.5 Meta-files

In this section, we'll be tidying up the `.emacs.d/` directory — by default, many Emacs packages create files useful for themselves in our `user-emacs-directory`. This leads to undesirable clutter. Certain packages create files that log recently visited files (2.5.1); log location of known projects (2.5.2); log location in recently visited files (2.5.3) The commonality between all these files is that they tend to reference... other files. Thus, I decided to refer to them as meta-files. First, let's designate a folder to collect our meta-files together:

```
(setq sd-meta-files-location (concat user-emacs-directory  
  ↪ "meta/"))
```

2.5.1 Recently visited files

```
(setq recentf-save-file (concat  
  sd-meta-files-location  
  "recentf"))
```

2.5.2 Projects' bookmarks

```
(setq projectile-known-projects-file (concat  
  sd-meta-files-location  
  "projectile-bookmarks.eld"  
  ↪ ))
```


2.5.3 Location in previously visited file

```
(setq save-place-file (concat
                        sd-meta-files-location
                        "places"))
```

2.5.4 Custom file

Load settings created automatically by GNU Emacs Custom. (For example, any clickable option/toggle is saved here.) Useful for fooling around with M-x customize-group <package>.

```
(setq custom-file (concat user-emacs-directory "custom.el"))
(load custom-file)
```

2.6 Backups

Backups are very important!

```
(setq backup-directory-alist
      `(("*" . ,temporary-file-directory))
      auto-save-file-name-transforms
      `(("*" . ,temporary-file-directory t))
      backup-by-copying t ; Don't delink hardlinks
      version-control t ; Use version numbers on backups
      delete-old-versions t ; Automatically delete excess
      ↪ backups
      kept-new-versions 20 ; how many of the newest versions
      ↪ to keep
      kept-old-versions 5) ; and how many of the old
```

2.7 Initial and default frames

We set the dimensions of the initial frame:

```
(add-to-list 'initial-frame-alist '(width . 70))
(add-to-list 'initial-frame-alist '(height . 40))
```

We also set the dimensions of subsequent frames:

```
(add-to-list 'default-frame-alist '(width . 70))
(add-to-list 'default-frame-alist '(height . 40))
```

Transparency.

```
(set-frame-parameter (selected-frame) 'alpha '(<active> . <inactive>))
(set-frame-parameter (selected-frame) 'alpha <both>)
```

```
(set-frame-parameter (selected-frame) 'alpha '(95 . 90))  
(add-to-list 'default-frame-alist '(alpha . (95 . 90)))
```

2.8 Secrets

The code contained in the `secrets.org` file is loaded by Emacs, but not rendered in this PDF for the sake of privacy. It contains individually identifying information such as names and e-mail addresses, which are used to populate Org templates (Section 5). You need to create this `secrets.org` file, as it is ignored by `git` by default.

```
(let ((secrets (concat user-emacs-directory "secrets.org")))  
  (when (file-exists-p secrets) (org-babel-load-file secrets)))
```

3 Keyboard shortcuts

What follows are the most useful keybindings, as well as the keybindings to the functions we defined ourselves. It doesn't matter if we haven't defined the functions themselves yet; Emacs will accept a keybinding for any symbol and does not check if the symbol's function definition exists, until the keybinding is pressed.

3.1 CUA mode

The following bindings strive to further enhance CUA mode.⁵

```
(cua-mode)
```

3.2 Files

3.2.1 Save a file

```
(global-set-key (kbd "C-s") 'save-buffer)
```

3.2.2 Open a file

```
(global-set-key (kbd "C-o") 'find-file)
```

3.2.3 List open files

```
(global-set-key (kbd "C-b") 'ivy-switch-buffer)
```

3.2.4 Open this very file

(Function defined in Section 2.4)

```
(global-set-key (kbd "C-c c") 'my/find-literate-config)
```

⁵Common User Access. This is a term coined by IBM which has influenced user navigation cues on all modern desktop OSes. From IBM's CUA, we get the `Ctrl-c` and `Ctrl-v` keyboard shortcuts.

3.2.5 Open a recently visited file

```
(global-set-key (kbd "C-r") 'counsel-recentf)
```

3.2.6 Locate a file

```
(global-set-key (kbd "C-c l") 'counsel-locate)
```

3.2.7 Open the agenda

```
(global-set-key (kbd "C-c a") 'org-agenda)
```

3.2.8 Open the diary

```
(global-set-key [f9]
  '(lambda ()
    "Load `org-agenda-diary-file'."
    (interactive)
    (find-file org-agenda-diary-file)))
```

3.2.9 Open Org mode document properties

```
(global-set-key [f9] 'sd-document-properties)
```

3.3 Windows

3.3.1 Close window and quit

The following bindings lead to more natural window & frame exit behaviors.

```
(global-set-key (kbd "C-w") 'sd-delete-window-or-previous-buffer)
```

3.4 Frame

3.4.1 Make new frame

```
(global-set-key (kbd "C-n") 'make-frame)
```

3.4.2 Make only frame

```
(global-set-key (kbd "C-`") 'delete-other-windows)
```

3.4.3 Delete frame or kill Emacs

```
(global-set-key (kbd "C-q") 'sd-delete-frame-or-kill-emacs)
```

3.4.4 Remap C-z when using a graphical interface

By default, C-z suspends the editor. This is extremely handy when the editor is started with the -nw option (no window, i.e. launched in a terminal), because it returns control to the terminal command line without quitting Emacs—it simply places the Emacs process in the background. The user may then use the Linux job management tools to return inside the Emacs process.

However, when using a graphical display, we have no need for suspending the frame, so we remap C-z to the much more sensible undo behaviour.

```
(when (display-graphic-p)
  (global-set-key (kbd "C-z") 'undo))
```

3.5 Text display

3.5.1 Zoom

The typical binding on both GNU/Linux and MS Windows is adequate here: C-= to zoom in, C-- to zoom out.

It seems that starting with Emacs 27.1, Control + mousewheel works.

```
(global-set-key (kbd "C--") 'text-scale-decrease)
(global-set-key (kbd "C-=") 'text-scale-increase)
(global-set-key (kbd "C-+") 'text-scale-increase)
```

3.6 TODO Navigation

Alt (Meta) is the privileged key for motion in a buffer. It is followed by an optional numerical argument, and a movement command. You may navigate in a buffer by keeping Alt pressed, optionally inputting a number from the keypad or number row, then pressing any of the following movement keys: j, k, h, and l. You will move in that direction in the amount of the numerical argument.

Table 1: Navigation keybindings.

	Backwards	Forwards
Character	M-h	M-l
Line	M-k	M-j
Word	M-f	M-b
Paragraph	M-a	M-e

We prevent Org mode from overriding preferred navigation keys.

```
(add-hook 'org-mode
  '(lambda ()
    (local-unset-key (kbd "M-j"))))
```

```
(local-unset-key (kbd "M-k"))  
(local-unset-key (kbd "M-l"))  
(local-unset-key (kbd "M-h"))))
```

3.6.1 Move down one line

```
(global-set-key (kbd "M-j") 'next-line)
```

3.6.2 Move up one line

```
(global-set-key (kbd "M-k") 'previous-line)
```

3.6.3 Move left one character

```
(local-unset-key (kbd "M-h"))  
(global-set-key (kbd "M-h") 'left-char)
```

3.6.4 Move right one character

```
(global-set-key (kbd "M-l") 'right-char)
```

3.7 Accessing customization

3.7.1 Customize a variable

```
(global-set-key (kbd "C-c v") 'customize-variable)
```

3.7.2 Customize a face

```
(global-set-key (kbd "C-c f") 'customize-face)
```

3.8 One-click workflows

A major advantage of the Emacs document production system: arbitrarily complicated functions can be assigned to very simple keybindings. This means we can automate workflows up to a pretty absurd level.

3.8.1 Export to PDF

PDF is probably the most prevalent file format for sharing static documents.

1. Document

```
(global-set-key (kbd "C-p") 'sd-quick-export)
```

2. **TODO** Presentation

3.8.2 Indent buffer

Indent buffer in every mode.

```
(global-set-key [f12]
  '(lambda ()
    "Clean up buffer in the most general sense.
This means indenting the buffer according to the major mode in
↳ force,
as well as deleting trailing whitespaces."
    (interactive)
    (sd-indent-buffer)
    (delete-trailing-whitespace)))
```

3.8.3 TODO Beautify Org mode buffer

Not only indent, but also clean up superfluous newlines.

```
(local-set-key [f12] 'sd-org-beautify)
```

4 Packages

Packages are collections of .el files providing added functionality to Emacs.

4.1 Meta

How do we bootstrap packages? First, let's figure out:

1. Where we get our packages from
2. How we upgrade packages
3. How we ensure our required packages are installed

4.1.1 Package archives

List of package archives.

```
(require 'package)
(add-to-list 'package-archives '("melpa" .
↳ "https://melpa.org/packages/") t)
(add-to-list 'package-archives '("org" .
↳ "https://orgmode.org/elpa/") t)
(package-initialize)
```

4.1.2 TODO Convenient package update

One-function rollup of upgradeable package tagging, download and lazy install.

4.1.3 use-package

We ensure use-package is installed, as well as all packages described in this configuration file.

```
(unless (package-installed-p 'use-package)
  (package-refresh-contents)
  (package-install 'use-package)
  (eval-when-compile (require 'use-package)))
(setq use-package-always-ensure t)
(require 'use-package)
(require 'bind-key)
```

4.2 evil-mode

Forgive me, for I have sinned.

This is the 2nd most significant customization after org-mode. Enabling evil-mode completely changes editing keys.⁶

```
(use-package evil)
(setq evil-toggle-key "C-c d")
(evil-mode 1)
```

4.3 Spelling, completion, and snippets

The following customizations open the doors to vastly increased typing speed and accuracy.

4.3.1 Syntax checking

We require a package to highlight syntax errors and warnings. The flycheck package ensures we are aware of all our code's syntactical shortcomings.

```
(use-package flycheck)
(global-flycheck-mode)
```

4.3.2 Spelling

```
(use-package flyspell)
(add-hook 'text-mode-hook 'flyspell-mode)
```

⁶For more information on vi keybindings, visit <https://hea-www.harvard.edu/~fine/Tech/vi.html>.

4.3.3 Completion

```
(use-package company)
(add-hook 'after-init-hook 'global-company-mode)
```

4.3.4 Insert template from keyword

Thanks to yasnippet, we can type certain keywords, then press TAB, to automatically insert a predefined text snippet. We can then navigate through the snippet by using <tab> (next field) and <backtab> (previous field).⁷

For instance: typing src then pressing TAB will expand the keyword to the following text:

```
#+BEGIN_SRC emacs-lisp :tangle yes

#+END_SRC
```

We notice that emacs-lisp is highlighted — this is the first modifiable field. Many clever programming tricks can be performed with yasnippet to save us a ton of time with boilerplate text!

```
(use-package yasnippet)
(yas-global-mode 1)
```

4.3.5 Delete all consecutive whitespaces

```
(use-package hungry-delete)
(global-hungry-delete-mode)
```

4.4 Utilities

4.4.1 Versioning of files

Wonderful Git porcelain for Emacs. Enables the administration of a Git repository in a pain-free way.

```
(use-package magit
  :bind ("C-c g" . magit-status))
```

4.4.2 Navigate between projects

This enables us to better manage our .git projects.

```
(use-package projectile
  :bind ("C-c p" . 'projectile-command-map)
  :init (projectile-mode 1)
  (setq projectile-completion-system 'ivy))
```

⁷<backtab> is synonymous with pressing shift-tab.

4.4.3 Display keyboard shortcuts on screen

```
(use-package which-key
  :init (which-key-mode))
```

4.4.4 Jump to symbol's definition

dumb-jump is a reliable symbol definition finder. It uses different matching algorithms and heuristics to provide a very educated guess on the location of a symbol's definition.

```
(use-package dumb-jump)
(add-hook 'xref-backend-functions #'dumb-jump-xref-activate)
```

4.4.5 Graphical representation of file history

```
(use-package undo-tree)
(global-undo-tree-mode)
```

4.4.6 Auto-completion framework

```
(use-package ivy
  :config (setq ivy-use-virtual-buffers t
                ivy-count-format "%d/%d "
                enable-recursive-minibuffers t))
(ivy-mode t)
```

1. Smartly suggesting interactive search matches

And he will be called Wonderful **Counselor**, Mighty God, Everlasting Father, Prince of Peace.

```
(use-package counsel
  :bind ("M-x" . counsel-M-x)
  :config (counsel-mode t))
```

2. Searching for items in current buffer

```
(use-package swiper
  :bind (("C-f" . swiper)))
```

4.4.7 Web browsing

Thanks Xah!⁸

⁸http://ergoemacs.org/emacs/emacs_set_default_browser.html

```
;; use browser depending on url
(setq
 browse-url-browser-function
 '(
  ("wikipedia\\.org" . browse-url-firefox)
  ("github" . browse-url-chromium)
  ("thefreedictionary\\.com" . eww-browse-url)
  (". " . browse-url-default-browser)
 ))
```

4.4.8 IRC

Emacs ships with an IRC client called `erc`.

```
(use-package erc
 :custom
 (erc-autojoin-channels-alist '(("freenode.net"
                                "#linux"
                                "#archlinux"
                                "#emacs"
                                "#bitcoin"
                                "#latex"
                                "#org-mode"
                                "#python"))))
(erc-autojoin-timing 'ident) ; Autojoin after NickServ
↪ identification.
(erc-fill-function 'erc-fill-static)
(erc-fill-static-center 16)
;; (erc-hide-list '("JOIN" "PART" "QUIT"))
(erc-lurker-hide-list '("JOIN" "PART" "QUIT"))
(erc-lurker-threshold-time (* 3600 4)) ; Four hours
(erc-prompt-for-nickserve-password nil)
(erc-server-reconnect-attempts 5)
(erc-server-reconnect-timeout 3)
:config
(add-to-list 'erc-modules 'spelling)
(erc-services-mode 1)
(erc-update-modules))
```

4.4.9 TODO Telegram

Yeah, a Telegram client exists for Emacs.

```
(use-package telega
 :load-path "~/telega.el/telega.el"
```

```
:commands (telega)
:defer t)
```

4.5 Coding languages

4.5.1 TODO Emacs Lisp

4.5.2 Python

Python is included by default on most Linux distributions.

```
(use-package py-yapf)
(add-hook 'python-mode-hook 'py-yapf-enable-on-save)
```

4.6 File formats

4.6.1 csv and Excel

```
(use-package csv-mode)
```

4.6.2 Interacting with PDFs

Org mode shines particularly when exporting to PDF — Org files can reliably be shared and exported to PDF in a reproducible fashion.

```
(use-package pdf-tools)
(pdf-tools-install)
```

4.6.3 Accounting

Ledger is a creation of John Wiegley's. It enables double-entry accounting in a simple plaintext format, and reliable verification of account balances through time.⁹

```
(use-package ledger-mode
:bind
("C-c r" . ledger-report)
("C-c C" . ledger-mode-clean-buffer))
```

These reports can be generated within Emacs. It is quite useful to pipe their output to an automated “smart document”.

```
(setq ledger-reports
'(("bal" "%(binary) -f %(ledger-file) bal")
  ("bal-USD" "%(binary) -f %(ledger-file) bal --exchange
  ↳ USD"))
```

⁹For more information, visit <https://www.ledger-cli.org/>.

```
(
  "reg" "%(binary) -f %(ledger-file) reg"
  "net-worth" "%(binary) -f %(ledger-file) bal ^Assets
  ↪ ^Liabilities --exchange USD"
  "net-income" "%(binary) -f %(ledger-file) bal ^Income
  ↪ ^Expenses --exchange USD --depth 2 --invert"
  "payee" "%(binary) -f %(ledger-file) reg @%(payee)"
  "account" "%(binary) -f %(ledger-file) reg %(account)"
  "budget" "%(binary) -f %(ledger-file) budget --exchange
  ↪ USD"
))
```

4.6.4 Plotting & charting

```
(use-package gnuplot)
```

4.7 Cosmetics

4.7.1 Start page

We replace the standard welcome screen with our own.

4.7.2 Better parentheses

```
(use-package rainbow-delimiters
  :config (add-hook 'prog-mode-hook #'rainbow-delimiters-mode))
(show-paren-mode 1)
```

4.7.3 Highlight *color* keywords in that color

This highlights hexadecimal numbers which look like colors, in that same color.

```
(use-package rainbow-mode
  :init
  (add-hook 'prog-mode-hook 'rainbow-mode))
```

4.7.4 Minor modes in mode line

We hide minor modes in the mode line.

```
(use-package rich-minority)
(rich-minority-mode 1)
(setf rm-whitelist "projectile")
```

4.7.5 Emojis

Emojis are a symbol of modernity, and their tasteful use enables communicating with people from around the world — we're all for that! B-) 😊

```
(when (string-equal system-type "gnu/linux")
  (use-package emojiify
    :hook (after-init . global-emojiify-mode)))
```

5 org-mode

Org mode is so significant that this section of the paper deserves its own introduction.

5.1 Introduction

Phew, after all this initialization, I can finally introduce Org mode! I am so **excited**.

Org mode replaces a word processor, a presentation creator, and a spreadsheet editor. The spreadsheet ability captures more than 80% use cases wherein one wishes to include a table in a text document destined for physical publication. (It is clear that Excel spreadsheets are *not* destined for physical publication — simply attempt to print an Excel spreadsheet with the default settings.) In my opinion, Org mode matches all *useful* features of the Microsoft Office suite 1-to-1.

What follows are customizations designed to make Org mode behave more like Microsoft Word. The end goal is, once again, to draw as many new users to Emacs as possible!

Check out how much information Org mode keeps concerning the most recent header:

```
(save-excursion
  (org-previous-visible-heading 1)
  (org-entry-properties))
```

(This block was evaluated on Microsoft Windows.)

```
((("CATEGORY" . "smart-documents")
  ("BLOCKED" . ""))
  ("FILE" . "c:/Users/blend/AppData/Roaming/.emacs.d/smart-documents.org")
  ("PRIORITY" . "A")
  ("ITEM" . "Introduction"))
```

5.2 Basic customization

5.2.1 Base folder

Org base directory is in user home on GNU/Linux, or in AppData in MS Windows.

```
(setq org-directory (concat user-emacs-directory "~/org"))
```

5.2.2 Prevent/warn on invisible edits

```
(setq org-catch-invisible-edits t)
```

5.3 Org cosmetics

First, we ensure the display of markup symbols for **bold**, *italic*, underlined and ~~strikethrough~~ text, and ensure our document appears indented upon loading.¹⁰

We then set values for many other Org-related cosmetic symbols.

```
(setq org-hide-emphasis-markers nil
      org-startup-indented t
      org-src-preserve-indentation nil
      org-edit-src-content-indentation 2
      org-ellipsis (propertize " " ; folding symbol
                                'mouse-face 'highlight
                                'help-echo "Unfold section."))
```

5.3.1 Pretty L^AT_EX symbols

We display L^AT_EX entities as UTF8 symbols ⇒ this is a slick idea to further make Emacs look like the exported PDF. Using symbols in tables is discouraged?

```
(setq org-pretty-entities t)
```

5.3.2 Dynamic numbering of headlines

We enable the dynamic numbering of headlines in an Org buffer. We also set the numbering face to `org-special-keyword`, which specifies a `:background white` attribute. This is necessary because otherwise, the background of the numbering may be overridden by the `TODO` face attribute `:background coral`.

```
(add-hook 'org-mode-hook 'org-num-mode)
(setq org-num-face 'org-special-keyword)
```

By default, we hide Org document properties such as `#+TITLE`, `#+AUTHOR`, and `#+DATE`, because those keywords are defined when the document template is populated. We can nevertheless always access those properties and edit them manually, with a simple keyboard shortcut (cf. Section 3.2.9).

¹⁰It *appears* indented, but the underlying plaintext file does not contain tab characters!

5.3.3 Document properties

```
(defun org-property-value (property)
  "Return the value of a given Org document property."
  (interactive)
  (save-excursion
    (goto-char (point-min))
    (re-search-forward
      (concat
        "^[:space:]*#\\\\"
        property
        ":[[:space:]]*\\(.\\(?:?\\\\"
        nil t)
      (nth 3 (car (cdr (org-element-at-point)))))))

(defun sd-document-properties ()
  "Open separate buffer to edit Org mode properties."
  (interactive)
  (let ((title (car (org-property-value "TITLE")))
        (date (org-property-value "DATE")))
    (with-output-to-temp-buffer "Smart Document Properties"
      (print title)
      (print date))))

(add-hook 'org-src-mode-hook
  '(lambda ()
     "Disable flycheck for `emacs-lisp-mode'."
     (setq-local flycheck-disabled-checkers
       '(emacs-lisp-checkdoc))))
```

5.3.4 Timestamps

More literary timestamps are exported to \LaTeX using the following custom format:

```
(setq org-time-stamp-custom-formats
  '("%d %b. %Y (%a)" . "%d %b. %Y (%a), at %H:%M"))
```

5.3.5 Sequence of TODOs

```
(setq org-todo-keywords
  '((sequence "TODO" "|" "DONE")
    (sequence "STUCK" "WAITING" "|" "N/A" "COMPLETED")
    (sequence "CONSTRUCTION" "REVIEWED" "|" "INSTALLED")))

(setq org-todo-keyword-faces
```

```
'(("STUCK" . (:height 1.6 :background "red" :foreground
→ "white" :weight bold))
("WAITING" . (:height 1.6 :background "yellow"))
("N/A" . (:height 1.6 :background "LightSteelBlue3"
→ :foreground "white"))
("COMPLETED" . (:height 1.6 :background "green"
→ :foreground "white"))))
```

5.4 Programming a Smart Documents

The following languages can be used inside SRC blocks, in view of being executed by the Org Babel backend upon document export.

```
(setq org-babel-load-languages
'((shell . t)
  (python . t)
  (plantuml . t)
  (emacs-lisp . t)
  (awk . t)
  (ledger . t)
  (gnuplot . t)
  (latex . t)))

(org-babel-do-load-languages
 'org-babel-load-languages '((C . t)
                              (shell . t)
                              (gnuplot . t)))
```

5.5 Agenda

The agenda displays a chronological list of headings across all agenda files for which the heading or body contain a matching org-time-stamp.¹¹

We open the agenda in a separate window.

```
(setq org-agenda-window-setup 'other-frame)
```

5.6 L^AT_EX export

We'll be compiling our documents with LuaTeX. This will afford us some future-proofing, since it was designated as the successor to pdfTeX by the latter's creators.

First, we define the command executed when an Org file is exported to L^AT_EX. We'll use latexmk, the Perl script which automatically runs binaries related to L^AT_EX in the correct order and the right amount of times.

Options and why we need them:

¹¹An org-time-stamp can be inserted with C-c . (period)

-shell-escape required by minted to color source blocks

-pdflatex=lualatex we use lualatex to generate our PDF

-interaction=nonstopmode go as far as possible without prompting user for input

```
(setq org-latex-pdf-process
  '("latexmk -pdf -f \
-pdflatex=lualatex -shell-escape \
-interaction=nonstopmode -outdir=%o %f"))
```

5.6.1 Exporting timestamps

We customize the format for org time stamps to make them appear monospaced in our exported \LaTeX documents. This makes them visually distinguishable from body text.

```
(setq org-latex-active-timestamp-format
  "\\texttt{%s}")
(setq org-latex-inactive-timestamp-format
  "\\texttt{%s}")
```

5.6.2 \LaTeX packages

The following packages are loaded for every time we export to \LaTeX .

```
(setq org-latex-packages-alist
  '(("AUTO" "babel" t
    ("pdflatex")))
  ("AUTO" "polyglossia" t ; Babel replacement for LuaLaTeX
    ("xelatex" "lualatex")))
  (" " "fontspec" t ; Fonts for LuaLaTeX
    ("lualatex")))
  (" " "booktabs" t ; Publication quality tables
    ("pdflatex" "lualatex")))
  (" " "wasysym" t ; Emojis and other symbols
    ("pdflatex" "lualatex")))
  (" " "lettrine" t
    ("pdflatex" "lualatex")))
  ("table,svgnames" "xcolor" t ; svgnames opens up ~150
    ↪ new color keywords
    ("pdflatex" "lualatex")))
  ("skip=0.5\\baselineskip" "caption" t ; Increase space
    ↪ between floats and captions
    ("pdflatex" "lualatex"))))
```

5.6.3 Colored source blocks in PDF export

Little bonus for GNU/Linux users: syntax highlighting for source code blocks in \LaTeX exports.

```
(when (string-equal system-type "gnu/linux")
  (add-to-list 'org-latex-packages-alist '("AUTO" "minted" t
                                           ("pdflatex"
                                            ↪ "lualatex"))))

(setq org-latex-listings 'minted)
(setq org-latex-minted-options '(("style" "friendly")
                                  ("breaklines" "true")
                                  ("breakanywhere" "true"))))
```

5.6.4 Cleaning directory after export

Now, we set the files to be deleted when a $\LaTeX \rightarrow$ PDF compilation occurs. We only care about two files, in the end: the Org mode file for edition, and the PDF for distribution.

```
(setq org-latex-logfiles-extensions
  '("aux" "bcf" "blg" "fdb_latexmk"
    "fls" "figlist" "idx" "log" "nav"
    "out" "ptc" "run.xml" "snm" "toc" "vrb" "xdv"
    "tex" "lot" "lof"))
```

5.6.5 Chronological diary entries

By default, Org agenda inserts diary entries as the first under the selected date. It is preferable to insert entries in the order that they were recorded, i.e. chronologically.

```
(setq org-agenda-insert-diary-strategy 'date-tree-last)
```

5.6.6 Extra \LaTeX class

This *letter* template completes the other default \LaTeX classes.

```
(require 'ox-publish)
(add-to-list 'org-latex-classes
  '("letter"
    "\\documentclass[11pt]{letter}"
    ("\\chapter{%s}" . "\\chapter*{%s}")
    ("\\section{%s}" . "\\section*{%s}")
    ("\\subsection*{%s}" . "\\subsection*{%s}")
    ("\\subsubsection*{%s}" .
     ↪ "\\subsubsection*{%s}")))
```

5.6.7 Table of contents

By default, body text can immediately follow the table of contents. It is however cleaner to separate table of contents with the rest of the work.

```
(setq org-latex-toc-command "\\tableofcontents\\clearpage")
```

The following makes TODO items appear red and CLOSED items appear green in Org's L^AT_EX exports. Very stylish, much flair!

5.6.8 AUCTEX

```
(use-package tex
  :defer t
  :ensure auctex
  :ensure auctex-latexmk
  :config
  (setq TeX-auto-save t))

(auctex-latexmk-setup)
```

5.6.9 Groff export

```
(require 'ox-groff)
```

5.7 TODO Org links

This is a mind-bending capacity of Org mode: we can assign arbitrary functions to be executed when a user follows an Org link. Org links appear like hyperlinks both in buffers and PDF exports — e.g. the following link to this very section, Section 5.7 — but their in-buffer behavior can be arbitrarily assigned.

```
(org-add-link-type
 "tag" 'endless/follow-tag-link)

(defun endless/follow-tag-link (tag)
  "Display a list of TODO headlines with tag TAG.
With prefix argument, also display headlines without a TODO
↪ keyword."
  (org-tags-view (null current-prefix-arg) tag))

[[tag:work+phonenumber-boss][Optional Description]]
```

6 One-click workflows

In this section, we'll implement useful one-click workflows. It comes later keybinding definitions for two reasons:

1. To a new user, keybindings are more important than the precise implementation of the bound function — it is more important to know how to drive a car than how a car works.
2. If the following subsections share the same name as the keybinding subsection (Section 3), the links will resolve to the earliest heading in the document, i.e. the keybinding subsection and not the subsection describing the 'one-click workflow'.

6.1 TODO Export to PDF

This reimplements the most common Org mode export: $\text{Org} \rightarrow \text{\LaTeX} \rightarrow \text{PDF}$. The binding is defined in Section 3.8.1.

6.1.1 From Org mode

```
(defun sd-quick-export--org ()
  "Org mode async export to PDF and open.
  This basically reimplements `C-c C-e C-a l o'."
  (org-open-file (org-latex-export-to-pdf)))
```

6.1.2 From a Ledger report

```
(defun sd-quick-export--ledger-report ()
  "Quick export for `ledger-mode' report buffers."
  (let ((old-buffer (current-buffer)))
    (with-output-to-temp-buffer "**SD Export**"
      (print "#+SETUPFILE:
      ↪ ~/.emacs.d/templates/documents/default.org")
      (newline)
      (insert-buffer-substring old-buffer)
      (forward-line 10)
      (org-table-convert-region (point) (goto-char (point-max)))
      (setq more-lines-p t)
      (while more-lines-p
        (move-end-of-line 1)
        (newline)
        (setq more-lines-p (= 0 (forward-line 1))))
      (org-open-file (org-latex-export-to-pdf)))))
```

6.1.3 From Nroff mode

```
(defun sd-quick-export--nroff (macros)
  "Export Nroff/Groff buffer, with specified macro set."
  (interactive "sMacro set used:")
  macros)
(shell-command
 (format "groff -%s -Tpdf %s | ps2pdf - > %s"
         macros
         (buffer-file-name)
         (concat (file-name-sans-extension buffer-file-name)
                  ".pdf"))))
```

6.1.4 Quick export

```
(defun sd-quick-export ()
  "Quickly prettify and export current buffer to PDF."
  (interactive)
  (cond ((eq major-mode 'org-mode)
         (sd-quick-export--org))
        ((eq major-mode 'nroff-mode)
         (sd-quick-export--nroff macros))
        ((eq major-mode 'emacs-lisp-mode)
         (message "No quick-export implemented yet."))
        ((eq major-mode 'ledger-report-mode)
         (sd-quick-export--ledger-report))
        (t (message (format "No sd-quick-export backend for %s."
                             major-mode))))))
```

6.2 Beautify buffer

Binding defined in Section 3.8.2.

```
(defun sd-indent-buffer ()
  "Indent entire buffer."
  (interactive)
  (save-excursion
    (indent-region (point-min) (point-max) nil)))

(defun sd-org-beautify ()
  "Beautify Org mode buffer."
  (interactive)
  (when (eq major-mode 'org-mode)
    (sd-indent-buffer)))
```

6.3 Smart window quitting

```
(defun sd-delete-window-or-previous-buffer ()  
  "Delete window; if sole window, previous buffer."  
  (interactive)  
  (if (> (length (window-list)) 1)  
      (delete-window)  
      (previous-buffer)))
```

6.4 Smart frame quitting

```
(defun sd-delete-frame-or-kill-emacs ()  
  (interactive)  
  "delete frame; if sole frame, kill Emacs."  
  (if (> (length (frame-list)) 1)  
      (delete-frame)  
      (save-buffers-kill-terminal)))
```

7 Editing preferences

These customizations enhance editor usability. They also encompass cosmetic changes not brought about a specific package.

7.1 Editor

7.1.1 Coding standards

This is just a better default. Don't @ me.

```
(setq c-default-style "linux"  
      c-basic-offset 4)
```

7.1.2 Recent files

The keybinding for opening a recently visited file is described in paragraph 3.2.5.

```
(recentf-mode 1)  
(setq recentf-max-menu-items 100)  
(setq recentf-max-saved-items 100)  
(run-at-time nil (* 5 60) 'recentf-save-list)
```

7.1.3 Reload changed files silently

```
(global-auto-revert-mode)
```

7.2 Frame

7.2.1 Header & mode lines

1. **TODO** Icons We start by defining some icons we wish to include in our user interface. Emacs allows the usage of GIF images — this paves the way for UI elements which may be animated.

```
(defcustom sd-icon-loading
  (create-image
    (concat user-emacs-directory "img/icons/ellipsis.gif")
    'gif nil
    :scale 0.4)
  "The GIF representing \"loading\". Not animated by
  ↪ default."
  :type 'sexp
  :version "27.1"
  :group 'sd)

(defun sd-icon-loading ()
  "Insert an animated blue ellipsis."
  (insert-image sd-icon-loading)
  (image-animate sd-icon-loading 0 t))
```

2. Header line

In Org mode, the document header line will be the title of the document we are working on currently. We start by defining keybindings for our header line buttons for navigating through open windows.

```
(defvar sd-header-line-previous-buffer-keymap
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1] 'previous-buffer)
    map)
  "Keymap for what is displayed in the header line, with a
  ↪ single
  window.")

(defvar sd-header-line-kill-buffer-keymap
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1]
      ↪ 'kill-buffer-and-window)
    map)
  "Keymap for closing current window.")

(defvar sd-header-line-maximize-window-keymap
```

```

(let ((map (make-sparse-keymap)))
  (define-key map [header-line mouse-1]
    ↪ 'delete-other-windows)
  map)
"Keymap for maximizing the current window.")

(defvar sd-header-line-minimize-window-keymap
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1] 'delete-window)
    map)
  "Keymap for minimizing the current window.")

```

Now, we describe the actual format of the header line.

```

(setq-default
  header-line-format
  '(:eval
    (list
      (if (eq (length (window-list)) 1)
        (propertyize " "
          'face 'org-meta-line
          'mouse-face 'highlight
          'keymap sd-header-line-previous-buffer-
          ↪ keymap
          'help-echo "Return to previous window.")
        (list (propertyize " "
          'face 'org-meta-line
          'mouse-face 'org-todo
          'keymap sd-header-line-kill-buffer-
          ↪ keymap
          'help-echo "Close this window.")
          (propertyize " "
            'face 'org-meta-line
            'mouse-face 'highlight
            'keymap sd-header-line-maximize-win-
            ↪ dow-keymap
            'help-echo "Maximize this window.")
            (propertyize " "
              'face 'org-meta-line
              'mouse-face 'highlight
              'keymap sd-header-line-minimize-win-
              ↪ dow-keymap
              'help-echo "Minimize this
              ↪ window.))))))

```



```

    mode-line-buffer-identification)))

(image-animate sd-icon-loading 0 t)

```

3. Mode line

This interpretation of the ideal mode line is the result of carefully studying the default mode-line, as well as studying various customizations online.

```

(defvar sd-mode-line-lock-buffer-keymap
  (let ((map (make-sparse-keymap)))
    (define-key map [mode-line mouse-1] 'read-only-mode)
    map)
  "Keymap for locking/unlocking the current buffer.")

(setq-default
 mode-line-format
 (list
  mode-line-front-space
  '(:eval (if buffer-read-only
    (propertyize " "
      'keymap sd-mode-line-lock-buffer-
      ↪ keymap
      'help-echo "C-x C-q: unlock
      ↪ buffer.")
    (propertyize " "
      'keymap
      ↪ sd-mode-line-lock-buffer-keymap
      'help-echo "C-x C-q: lock
      ↪ buffer.")))
  '(:eval (if (buffer-modified-p)
    (propertyize " "
      'help-echo "Buffer is modified.")
    (propertyize " ✓ "
      'help-echo "Buffer is saved.")))
  mode-line-modes " "
  mode-line-end-spaces))

```

7.3 Window

7.4 Buffer

7.4.1 Save cursor location

Save cursor location in visited buffer after closing it or Emacs.

```

(save-place-mode 1)

```

7.4.2 Column filling

We leave the default `fill-column` unchanged, so as to minimally disrupt a user's existing documents. We automatically break lines longer than `fill-column`.

```
(add-hook 'org-mode-hook
          'turn-on-auto-fill)
```

7.5 Text

7.5.1 Beautiful symbols

We want the Emacs Lisp keyword `lambda` to be rendered as λ within the editor. This is mostly for a subjective “cool” factor.

```
(global-prettify-symbols-mode 1)
```

7.5.2 Org mode sugar

Let's pimp out the appearance of our text in Org mode. First, we prettify checkbox lists when viewed on GNU/Linux systems.

```
(when (string-equal system-type "gnu/linux")
  (add-hook 'org-mode-hook
    (lambda ()
      "Beautify Org symbols."
      (push '("[ ]" . "o") prettify-symbols-alist) ;
      ↪ Unchecked item
      (push '("[X]" . " " ) prettify-symbols-alist) ;
      ↪ Checked item
      (push '("[-]" . " " ) prettify-symbols-alist) ;
      ↪ Partially checked item
      (push '("-" . " " ) prettify-symbols-alist) ; DONE
      ↪ headings
      (prettify-symbols-mode))))
```

- ☐ This first item is unticked
- ☐ This second item is partially completed
 - ☒ This first sub-item is ticked
 - ☐ This sub-item is not ticked
- ☐ This third item is ticked

7.5.3 Electric modes

Electricity is a very important technology. In Emacs jargon, “electric” modes tend to automate behaviors or present some elegant simplification to a workflow.¹²

```
(electric-pair-mode) ; Certain character pairs are automatically
↳ completed.
(electric-indent-mode) ; Newlines are always intelligently
↳ indented.
```

7.6 Minibuffer

We replace the longer yes-or-no-p questions with more convenient y-or-n-p.

```
(defalias 'yes-or-no-p 'y-or-n-p)
```

Disable minibuffer scroll bar.

```
(set-window-scroll-bars (minibuffer-window) nil nil)
```

8 Themes

Without a carefully designed theme, our editor would become unusable. Thus, we *describe* two themes that were developed **purposefully** and iteratively.

```
(setq custom-theme-directory (concat user-emacs-directory
↳ "themes/"))
```

```
(load-theme 'sd-compagnon)
```

```
(load-theme 'molokai)
```

```
(load-theme 'sd-light)
```

```
(load-theme 'sd-dark)
```

8.1 My light and dark themes

A highly legible, unambiguous, and classic theme.

Table 2: Light and dark themes' colors.

Color	sd-light	sd-dark
Black	default text	default background
Lighter shades	lesser headers	<i>n/a</i>
White	default background	default text
Darker shades	<i>n/a</i>	lesser headers
Red	negative	<i>same</i>
Tomato	timestamp 'TODO'	<i>same</i>
Green	positive	<i>same</i>
ForestGreen	timestamp 'DONE'	<i>same</i>
Blue	interactive content; links	<i>same</i>
SteelBlue	anything Org mode; anchor color	<i>same</i>
DeepSkyBlue	highlight	<i>same</i>
DodgerBlue	isearch	<i>same</i>
Purple	Code syntax highlighting	<i>same</i>

8.1.1 Colors

The default face is a black foreground on a white background, this matches MS Word. We are striving for a simple, intuitive color scheme.

Most of the affordance cues derived from color are identical in both light and dark themes (Table 2).

1. Red
2. Green
3. Blue
4. Purple

Purple is Emacs' main logo color. Since we use Emacs for coding a lot, code syntax highlighting to could be in the pink/purple shades.

8.1.2 Cursors

In order to imitate other modern text editors, we resort to a blinking bar cursor. We choose red, the most captivating color, because the cursor is arguably the region on our screen:

1. most often looked at;
2. most often searched when lost.

¹²More information can be found at <https://www.emacswiki.org/emacs/Electricity>.

In files containing only fixed-pitch fonts (i.e. files containing only code), the cursor becomes a high-visibility box.

In files containing a mix of variable-pitch and fixed-pitch fonts, the cursor is a more MS Word-like bar.

```
(setq-default cursor-type 'bar)
```

8.1.3 TODO Fonts

Here are some fonts I discovered and enjoyed since I began learning Emacs.

1. Serif

Crimson Pro¹³ variable-pitch, default body text font

- Inspired by Garamond

Linux Libertine¹⁴ variable-pitch, default body text font

- Inspired by Garamond

2. Sans serif

Public Sans¹⁵ variable-pitch, default body text font

- Very modern yet neutral
- Designed for the U.S. government
- Exceptional color on screen

Jost¹⁶ org-document-title and org-level-1

- Ultra-modern
- Tasteful amount of geometric inspiration

Open Sans¹⁷ variable-pitch

- Ooh geometric Bauhaus influences, look at me
- Tall leading height is harmonious

Liberation Sans¹⁸ variable-pitch

- Metrically compatible with *Arial* (ugh)
- Unoffensive, unambitious forms
- Pretty angular letters, it's like you're trying to read squares

3. Monospace

¹³

¹⁴

¹⁵<https://public-sans.digital.gov/>

¹⁶<https://indestructibletype.com/Jost.html>

¹⁷<https://www.opensans.com/>

¹⁸https://en.wikipedia.org/wiki/Liberation_fonts

Hack¹⁹ default and fixed-pitch, default code font

- Legible, modern monospace font
- Strict, sharp, uncompromising

Hermit²⁰ org-block, anything Org/meta in general

- Slightly wider than Hack
- More opinionated shapes
- Very legible parentheses, very useful for Emacs Lisp!

Courier Prime²¹ monospace in print

4. Using proportional fonts when needed

We use variable-pitch-mode for appropriate modes.

```
(add-hook 'org-mode-hook 'variable-pitch-mode)
(add-hook 'info-mode-hook 'variable-pitch-mode)
```

5. **TODO** Default font size

Make default font size larger on displays of which the resolution is greater than 1920×1080.

```
(if (< screen-width 1920)
    (default-font)
    else)
```

8.2 **TODO** *Wealthy* document theme

GOOD golly, nobody wishes for a *pedestrian* theme! Let your entourage know that you're rocking an editor fit for a king with this finely crafted 'wealthy' theme. Selecting it shall enable the following fancitudes:

1. The default font shall be sublimed in the form of *EB Garamond*
2. Bullets will be tastefully replaced with pointing fingers
3. Heading stars will be replaced with Black Queen chess pieces

CLAUDE Garamont (c. 1510–1561), known commonly as **Claude Garamond**, was a French type designer, publisher and punch-cutter based in Paris. Garamond worked as an engraver of punches, the masters used to stamp matrices, the moulds used to cast metal type. He worked in the tradition now called old-style serif design, which produced letters with a

¹⁹<https://sourcefoundry.org/hack/>

²⁰<https://pcaro.es/p/hermit/>

²¹<https://quoteunquoteapps.com/courierprime/index.php>



Figure 1: Claude Garamont, an icon of font design. World-renowned for his elegant typefaces, which inspired many generations of typographers.

relatively organic structure resembling handwriting with a pen but with a slightly more structured and upright design. Considered one of the leading type designers of all time, he is recognised to this day for the elegance of his typefaces. Many old-style serif typefaces are collectively known as Garamond, named after the designer.

From https://en.wikipedia.org/wiki/Claude_Garamond

8.2.1 Symbol substitution

```
(defun sd-wealthy ()
  "Beautify symbols for our wealthy theme."
  (push '("-" . " ") prettify-symbols-alist) ; unnumbered
  ↪ bullets
  (push '("*" . " ") prettify-symbols-alist) ; headings
  (prettify-symbols-mode))
```

8.3 TODO minimal

9 Late setup

At this point, our editor is almost ready to run. Phew! All that's left to do is to interrupt our profiling activities, and smartly store the result of our profiling.

9.1 Profiling — stop

```
(profiler-stop)
```

9.2 Profiling—report

(`profiler-report`)

10 Conclusion

In this configuration file, we described a series of customization steps taken to make Emacs more palatable to modern word processors users.