

Smart Documents

Marius Peter

<2020-12-19 Sat>

Contents

1	Introduction	6
1.1	TODO User details	7
1.2	File system paths	7
2	Early setup	7
2.1	The first file to load	7
2.2	The second file to load	8
2.3	Profiling — start	8
2.4	Jumping to this file	8
2.5	Speeding up the next startup	9
2.6	Meta-files	9
2.6.1	Recently visited files	9
2.6.2	Projects' bookmarks	9
2.6.3	Location in previously visited file	9
2.6.4	Custom file	10
2.7	Backups	10
2.8	Initial and default frames	10
2.9	Secrets	11
3	Keyboard shortcuts	11
3.1	CUA mode	11
3.2	Files	11
3.2.1	Save a file	11
3.2.2	Open a file	11
3.2.3	List open files	11
3.2.4	Open this very file	12
3.2.5	Open a recently visited file	12
3.2.6	Locate a file	12
3.2.7	Open the agenda	12
3.2.8	Open the diary	12
3.2.9	Open Org mode document properties	12
3.3	Windows	12
3.3.1	Close window and quit	12
3.4	Frame	13
3.4.1	Make new frame	13
3.4.2	Make only frame	13
3.4.3	Delete frame or kill Emacs	13
3.4.4	Open sidebar	13
3.5	Text display	14

3.5.1	Zoom	14
3.6	TODO Navigation	14
3.6.1	Move down one line	14
3.6.2	Move up one line	15
3.6.3	Move left one character	15
3.6.4	Move right one character	15
3.7	Accessing customization	15
3.7.1	Customize a variable	15
3.7.2	Customize a face	15
3.8	One-click workflows	15
3.8.1	Export to PDF	15
3.8.2	Indent buffer	16
3.8.3	TODO Beautify Org mode buffer	16
4	Packages	16
4.1	Meta	16
4.1.1	Package archives	16
4.1.2	TODO Convenient package update	17
4.1.3	use-package	17
4.2	evil-mode	17
4.3	Spelling, completion, and snippets	17
4.3.1	Syntax checking	17
4.3.2	Spelling	18
4.3.3	Insert template from keyword	18
4.3.4	Complete anything interactively	18
4.3.5	Delete all consecutive whitespaces	18
4.4	Utilities	18
4.4.1	Versioning of files	18
4.4.2	Navigate between projects	19
4.4.3	Display keyboard shortcuts on screen	19
4.4.4	Jump to symbol's definition	19
4.4.5	Graphical representation of file history	19
4.4.6	Auto-completion framework	19
4.4.7	IRC	20
4.4.8	TODO Telegram	20
4.5	Coding languages	21
4.5.1	TODO Emacs Lisp	21
4.5.2	Python	21
4.6	File formats	21
4.6.1	csv and Excel	21
4.6.2	Interacting with PDFs	21

4.6.3	Accounting	21
4.6.4	Plotting & charting	22
4.7	Cosmetics	22
4.7.1	Start page	22
4.7.2	TODO Sidebar	22
4.7.3	Better parentheses	23
4.7.4	Highlight <i>color</i> keywords in that color	23
4.7.5	Minor modes in mode line	23
4.7.6	Emojis	23
5	org-mode	24
5.1	Introduction	24
5.2	Basic customization	24
5.2.1	Base folder	24
5.2.2	Prevent/warn on invisible edits	24
5.3	Org cosmetics	25
5.3.1	Dynamic numbering of headlines	25
5.3.2	Document properties	25
5.3.3	Timestamps	26
5.4	Programming a Smart Documents	26
5.5	Agenda	27
5.6	L ^A T _E X export	27
5.6.1	Exporting timestamps	27
5.6.2	L ^A T _E X packages	28
5.6.3	Colored source blocks in PDF export	28
5.6.4	Cleaning directory after export	29
5.6.5	Chronological diary entries	29
5.6.6	Table of contents	29
5.7	TODO Org links	30
6	One-click workflows	30
6.1	TODO Export to PDF	30
6.2	Beautify buffer	31
7	Editing preferences	32
7.1	Editor	32
7.1.1	Coding standards	32
7.1.2	Recent files	32
7.2	Frame	32
7.2.1	Header & mode lines	32
7.3	Window	35

7.4	Buffer	35
7.4.1	Save cursor location	35
7.4.2	Column filling	36
7.5	Text	36
7.5.1	Beautiful symbols	36
7.5.2	Org mode sugar	36
7.5.3	Electric modes	37
7.6	Minibuffer	37
8	Themes	37
8.1	My light and dark themes	37
8.1.1	Colors	37
8.1.2	Cursors	39
8.1.3	Fonts	39
8.2	TODO Wealthy theme	40
8.2.1	Symbol substitution	41
8.3	TODO minimal	42
9	Late setup	42
9.1	Profiling — stop	42
9.2	Profiling — report	42
10	Conclusion	42
A	Unpacking our literate configuration	42

List of Figures

1	Claude Garamont, an icon of font design	41
---	---------------------------------------------------	----

List of Tables

1	Navigation keybindings	14
2	Light and dark themes' colors	38

Abstract

The idea of *Smart Documents* came to me as I was reflecting on how to improve the document creation process in my workplace. The GNU Emacs editor had captured my imagination and I wanted to create an accessible and highly productive text editor to benefit my organization. In this paper, I'll lay out my vision for the *Smart Document*, a file containing both text destined to the reader, and code describing how to update, validate, and present this text; then, I'll weave my personal GNU Emacs customizations with a tutorial. This paper is a *Smart Document* itself!

1 Introduction

GNU Emacs is most often used as a text editor. The utmost level of customization is afforded by the ability to rewrite *any* part of the source code and observe the editor's modified behavior in real time. Since its inception in 1984, GNU Emacs has grown to be much more than a full-featured, high-productivity text editor — new *modes* have been written to interact with hundreds of file formats, including `.txt`, `.pdf`, `.jpg`, `.csv`, and `.zip` just to name a few. This paper itself was written in *Org mode*, a collection of functions enabling the harmonious mixing of code and comments in view of publication: this is the endgame of *literate programming*, and the basis of my vision for *Smart Documents*.

The following sections were laid out very deliberately. When we start Emacs, the source code blocks contained in this document are evaluated sequentially — our editing environment is constructed in real time as we execute the blocks in order. For instance, we only begin loading packages once we ensured `use-package` is working properly.¹

Customizing Emacs goes far, far beyond rewriting sections of this document — feel free to experiment and discover. Here are three commands that will help you understand all the symbols in this file, if you are browsing this paper within Emacs itself:

C-h f describe function

C-h v describe variable

C-h k describe key

You can always press `f1` to access Emacs built-in help.

¹For more information on the detailed steps Emacs takes upon starting, refer to https://www.gnu.org/software/emacs/manual/html_node/elisp/Startup-Summary.html.

1.1 TODO User details

One advantage of working with *Smart Documents* is that they can automatically be populated with our details in the header, footer, or other appropriate element.

```
(setq user-full-name "Marius Peter")

(defun my/user-details-get ()
  "Get user details."
  (setq user-full-name (read-string "Enter full user name:"))
  (setq user-mail-address (read-string "Enter user e-mail
↪ address:"))
  (message "Successfully captured user details.))

(defun my/tokenize-user-details ()
  "Tokenize user details."

  (cons 'user-full-name user-full-name))

(unless (file-exists-p (concat user-emacs-directory
                              "meta/user-details"))
  (setq user-details '(user-full-name
                      user-mail-address))
  (append-to-file "Foobar\n" nil "~/.emacs.d/meta/foobar"))
```

1.2 File system paths

In this subsection, we tell Emacs about relevant paths to resources.

On my MS Windows machine, I add the path to Portable Git.²

```
(when (string-equal system-type "windows-nt")
  (add-to-list 'exec-path
↪ "C:/Users/marius.peter/PortableGit/bin/"))
```

2 Early setup

2.1 The first file to load

The contents of this Section was automatically moved to `~/.emacs.d/init.el`. Use 'sd-pack-section' to copy the contents back into this section.

²Download from <https://git-scm.com/download/win>

This is the very first user-editable file loaded by Emacs.³ In it, we disable GUI elements that would otherwise be loaded and displayed once Emacs is ready to accept user input.

It can be found here: `early-init.el`

2.2 The second file to load

Traditionally, file `~/.emacs` is used as the init file, although Emacs also looks at the following locations:

- `~/.emacs.el`
- `~/.emacs.d/init.el`
- `~/.config/emacs/init.el`.

From the GNU website⁴

This file can be found here: `init.el`

If no file is found, Emacs then loads in its purely vanilla state.

2.3 Profiling — start

We start the profiler now , and will interrupt it in Section 9.1. We will then present profiling report in Section 9.2.

```
; (profiler-start)
```

2.4 Jumping to this file

We begin by defining a function to open this very file.

```
(defun my/find-literate-config ()  
  "Jump to this very file."  
  (interactive)  
  (find-file (concat my/literate-config ".org")))
```

³This feature became available in version 27.1.

⁴https://www.gnu.org/software/emacs/manual/html_node/emacs/Init-File.html

2.5 Speeding up the next startup

```
(defun byte-compile-literate-config ()  
  "Byte compile our literate configuration file."  
  (delete-file (concat my/literate-config ".elc"))  
  (delete-file (concat my/literate-config ".el"))  
  (org-babel-tangle-file (concat my/literate-config ".org"))  
  (byte-compile-file (concat my/literate-config ".el")))  
  
(add-hook 'kill-emacs-hook 'byte-compile-literate-config)
```

2.6 Meta-files

In this section, we'll be tidying up the `.emacs.d/` directory — by default, many Emacs packages create files useful for themselves in our `user-emacs-directory`. This leads to undesirable clutter. Certain packages create files that log recently visited files (2.6.1); log location of known projects (2.6.2); log location in recently visited files (2.6.3) The commonality between all these files is that they tend to reference... other files. Thus, I decided to refer to them as meta-files. First, let's designate a folder to collect our meta-files together:

```
(setq sd-meta-files-location (concat user-emacs-directory  
  ↪ "meta/"))
```

2.6.1 Recently visited files

```
(setq recentf-save-file (concat  
  sd-meta-files-location  
  "recentf"))
```

2.6.2 Projects' bookmarks

```
(setq projectile-known-projects-file (concat  
  sd-meta-files-location  
  "projectile-bookmarks.eld"  
  ↪ ))
```

2.6.3 Location in previously visited file

```
(setq save-place-file (concat  
  sd-meta-files-location  
  "places"))
```

2.6.4 Custom file

Load settings created automatically by GNU Emacs Custom. (For example, any clickable option/toggle is saved here.) Useful for fooling around with `M-x customize-group <package>`.

```
(setq custom-file (concat user-emacs-directory "custom.el"))
(load custom-file)
```

2.7 Backups

Backups are very important!

```
(setq backup-directory-alist
      `(("*" . ,temporary-file-directory))
      auto-save-file-name-transforms
      `(("*" ,temporary-file-directory t))
      backup-by-copying t      ; Don't delink hardlinks
      version-control t       ; Use version numbers on backups
      delete-old-versions t   ; Automatically delete excess
      ↪ backups
      kept-new-versions 20    ; how many of the newest versions
      ↪ to keep
      kept-old-versions 5)    ; and how many of the old
```

2.8 Initial and default frames

We set the dimensions of the initial frame:

```
(add-to-list 'initial-frame-alist '(width . 70))
(add-to-list 'initial-frame-alist '(height . 40))
```

We also set the dimensions of subsequent frames:

```
(add-to-list 'default-frame-alist '(width . 70))
(add-to-list 'default-frame-alist '(height . 40))
```

Transparency.

```
;; (set-frame-parameter (selected-frame) 'alpha '(<active> .
↪ <inactive>))
;; (set-frame-parameter (selected-frame) 'alpha <both>)
(set-frame-parameter (selected-frame) 'alpha '(95 . 80))
(add-to-list 'default-frame-alist '(alpha . (95 . 80)))
```

2.9 Secrets

The code contained in the `secrets.org` file is loaded by Emacs, but not rendered in this PDF for the sake of privacy. It contains individually identifying information such as names and e-mail addresses, which are used to populate Org templates (Section 5). You need to create this `secrets.org` file, as it is ignored by `git` by default.

```
(let ((secrets (concat user-emacs-directory "secrets.org")))
  (when (file-exists-p secrets) (org-babel-load-file secrets)))
```

3 Keyboard shortcuts

What follows are the most useful keybindings, as well as the keybindings to the functions we defined ourselves. It doesn't matter if we haven't defined the functions themselves yet; Emacs will accept a keybinding for any symbol and does not check if the symbol's function definition exists, until the keybinding is pressed.

3.1 CUA mode

The following bindings strive to further enhance CUA mode.⁵

```
(cua-mode)
```

3.2 Files

3.2.1 Save a file

```
(global-set-key (kbd "C-s") 'save-buffer)
```

3.2.2 Open a file

```
(global-set-key (kbd "C-o") 'find-file)
```

3.2.3 List open files

```
(global-set-key (kbd "C-b") 'ivy-switch-buffer)
```

⁵Common User Access. This is a term coined by IBM which has influenced user navigation cues on all modern desktop OSes. From IBM's CUA, we get the `Ctrl-c` and `Ctrl-v` keyboard shortcuts.

3.2.4 Open this very file

(Function defined in Section 2.4)

```
(global-set-key (kbd "C-c c") 'my/find-literate-config)
```

3.2.5 Open a recently visited file

```
(global-set-key (kbd "C-r") 'counsel-recentf)
```

3.2.6 Locate a file

```
(global-set-key (kbd "C-c l") 'counsel-locate)
```

3.2.7 Open the agenda

```
(global-set-key [f5] 'org-agenda)
```

3.2.8 Open the diary

```
(global-set-key [f9]
  '(lambda ()
    "Load `org-agenda-diary-file'."
    (interactive)
    (find-file org-agenda-diary-file)))
```

3.2.9 Open Org mode document properties

```
(global-set-key [f9] 'sd-document-properties)
```

3.3 Windows

3.3.1 Close window and quit

The following bindings lead to more natural window & frame exit behaviors.

```
(global-set-key (kbd "C-w")
  (lambda ()
    "Delete window; if sole window, previous
    ↪ buffer."
    (interactive)
    (if (> (length (window-list)) 1)
```

```
(delete-window)
(previous-buffer)))
```

3.4 Frame

3.4.1 Make new frame

```
(global-set-key (kbd "C-n") 'make-frame)
```

3.4.2 Make only frame

```
(global-set-key (kbd "C-`") 'delete-other-windows)
```

3.4.3 Delete frame or kill Emacs

```
(global-set-key (kbd "C-q")
  (lambda ()
    (interactive)
    "delete frame; if sole frame, kill Emacs."
    (if (> (length (frame-list)) 1)
        (delete-frame)
        (kill-emacs))))
```

3.4.4 Open sidebar

We define bindings to open a sidebar at the left of the frame.

```
(global-set-key (kbd "<left-fringe> <mouse-1>")
  (lambda ()
    "Open the sidebar on the left side."
    (interactive)
    (sd-sidebar "left")))
(global-set-key (kbd "<right-fringe> <mouse-1>")
  (lambda ()
    "Open the sidebar on the right side."
    (interactive)
    (sd-sidebar "right")))
```

3.5 Text display

3.5.1 Zoom

The typical binding on both GNU/Linux and MS Windows is adequate here: `C--` to zoom in, `C+=` to zoom out.

It seems that starting with Emacs 27.1, Control + mousewheel works.

```
(global-set-key (kbd "C--") 'text-scale-decrease)
(global-set-key (kbd "C+=") 'text-scale-increase)
(global-set-key (kbd "C-+") 'text-scale-increase)
```

3.6 TODO Navigation

`Alt` (Meta) is the privileged key for motion in a buffer. It is followed by an optional numerical argument, and a movement command. You may navigate in a buffer by keeping `Alt` pressed, optionally inputting a number from the keypad or number row, then pressing any of the following movement keys: `j`, `k`, `h`, and `l`. You will move in that direction in the amount of the numerical argument.

Table 1: Navigation keybindings.

	Backwards	Forwards
Character	<code>M-h</code>	<code>M-l</code>
Line	<code>M-k</code>	<code>M-j</code>
Word	<code>M-f</code>	<code>M-b</code>
Paragraph	<code>M-a</code>	<code>M-e</code>

We prevent Org mode from overriding preferred navigation keys.

```
(add-hook 'org-mode
  '(lambda ()
    (local-unset-key (kbd "M-j"))
    (local-unset-key (kbd "M-k"))
    (local-unset-key (kbd "M-l"))
    (local-unset-key (kbd "M-h")))))
```

3.6.1 Move down one line

```
(global-set-key (kbd "M-j") 'next-line)
```

3.6.2 Move up one line

```
(global-set-key (kbd "M-k") 'previous-line)
```

3.6.3 Move left one character

```
(global-set-key (kbd "M-h") 'left-char)
```

3.6.4 Move right one character

```
(global-set-key (kbd "M-l") 'right-char)
```

3.7 Accessing customization

3.7.1 Customize a variable

```
(global-set-key (kbd "C-c v") 'customize-variable)
```

3.7.2 Customize a face

```
(global-set-key (kbd "C-c f") 'customize-face)
```

3.8 One-click workflows

A major advantage of the Emacs document production system: arbitrarily complicated functions can be assigned to very simple keybindings. This means we can automate workflows up to a pretty absurd level.

3.8.1 Export to PDF

PDF is probably the most prevalent file format for sharing static documents.

1. Document

```
(global-set-key (kbd "C-p") 'sd-quick-export)
```

2. TODO Presentation

3.8.2 Indent buffer

Indent buffer in every mode.

```
(global-set-key [f12]
  '(lambda ()
    "Clean up buffer in the most general sense.
This means indenting the buffer according to the major mode in
↪ force,
as well as deleting trailing whitespaces."
    (interactive)
    (sd-indent-buffer)
    (delete-trailing-whitespace)))
```

3.8.3 TODO Beautify Org mode buffer

Not only indent, but also clean up superfluous newlines.

```
(local-set-key [f12] 'sd-org-beautify)
```

4 Packages

Packages are collections of .el files providing added functionality to Emacs.

4.1 Meta

How do we bootstrap packages? First, let's figure out:

1. Where we get our packages from
2. How we upgrade packages
3. How we ensure our required packages are installed

4.1.1 Package archives

List of package archives.

```
(require 'package)
(add-to-list 'package-archives '("melpa" .
↪ "https://melpa.org/packages/") t)
(add-to-list 'package-archives '("org" .
↪ "https://orgmode.org/elpa/") t)
(package-initialize)
```


4.1.2 TODO Convenient package update

One-function rollup of upgradeable package tagging, download and lazy install.

4.1.3 use-package

We ensure use-package is installed, as well as all packages described in this configuration file.

```
(unless (package-installed-p 'use-package)
  (package-refresh-contents)
  (package-install 'use-package)
  (eval-when-compile (require 'use-package)))
(setq use-package-always-ensure t)
(require 'use-package)
(require 'bind-key)
```

4.2 evil-mode

Forgive me, for I have sinned.

This is the 2nd most significant customization after org-mode. Enabling evil-mode completely changes editing keys.⁶

```
(use-package evil)
; (setq evil-toggle-key "C-c d") ; devil...
; (evil-mode 1)
```

4.3 Spelling, completion, and snippets

The following customizations open the doors to vastly increased typing speed and accuracy.

4.3.1 Syntax checking

We require a package to highlight syntax errors and warnings. The flycheck package ensures we are aware of all our code's syntactical shortcomings.

```
(use-package flycheck)
(global-flycheck-mode)
```

⁶For more information on vi keybindings, visit <https://hea-www.harvard.edu/~fine/Tech/vi.html>.

4.3.2 Spelling

```
(use-package flyspell)
(add-hook 'text-mode-hook 'flyspell-mode)
```

4.3.3 Insert template from keyword

Thanks to yasnippet, we can type certain keywords, then press `TAB`, to automatically insert a predefined text snippet. We can then navigate through the snippet by using `<tab>` (next field) and `<backtab>` (previous field).⁷

For instance: typing `src` then pressing `TAB` will expand the keyword to the following text:

```
#+BEGIN_SRC emacs-lisp :tangle yes

#+END_SRC
```

We notice that `emacs-lisp` is highlighted — this is the first modifiable field. Many clever programming tricks can be performed with yasnippet to save us a ton of time with boilerplate text!

```
(use-package yasnippet)
(yas-global-mode 1)
```

4.3.4 Complete anything interactively

```
(use-package company)
(add-hook 'after-init-hook 'global-company-mode)
```

4.3.5 Delete all consecutive whitespaces

```
(use-package hungry-delete)
(global-hungry-delete-mode)
```

4.4 Utilities

4.4.1 Versioning of files

Wonderful Git porcelain for Emacs. Enables the administration of a Git repository in a pain-free way.

```
(use-package magit
:bind ("C-c g" . magit-status))
```

⁷`<backtab>` is synonymous with pressing `shift-tab`.

4.4.2 Navigate between projects

This enables us to better manage our .git projects.

```
(use-package projectile
  :bind ("C-c p" . 'projectile-command-map)
  :init (projectile-mode 1)
        (setq projectile-completion-system 'ivy))
```

4.4.3 Display keyboard shortcuts on screen

```
(use-package which-key
  :init (which-key-mode))
```

4.4.4 Jump to symbol's definition

dumb-jump is a reliable symbol definition finder. It uses different matching algorithms and heuristics to provide a very educated guess on the location of a symbol's definition.

```
(use-package dumb-jump)
(add-hook 'xref-backend-functions #'dumb-jump-xref-activate)
```

4.4.5 Graphical representation of file history

```
(use-package undo-tree)
(global-undo-tree-mode)
```

4.4.6 Auto-completion framework

```
(use-package ivy
  :config (setq ivy-use-virtual-buffers t
                ivy-count-format "%d/%d "
                enable-recursive-minibuffers t))
(ivy-mode t)
```

1. Smartly suggesting interactive search matches

And he will be called Wonderful **Counselor**, Mighty God, Everlasting Father, Prince of Peace.

```
(use-package counsel
  :bind ("M-x" . counsel-M-x)
  :config (counsel-mode t))
```

2. Searching for items

```
(use-package swiper
  :bind (("C-f" . swiper)))
```

4.4.7 IRC

Emacs ships with an IRC client called `erc`.

```
(use-package erc
  :custom
  (erc-autojoin-channels-alist '("freenode.net"
                                "#linux"
                                "#archlinux"
                                "#emacs"
                                "#bitcoin"
                                "#latex"
                                "#org-mode"
                                "#python")))
(erc-autojoin-timing 'ident) ; Autojoin after NickServ
                             ↪ identification.
(erc-fill-function 'erc-fill-static)
(erc-fill-static-center 16)
;; (erc-hide-list '("JOIN" "PART" "QUIT"))
(erc-lurker-hide-list '("JOIN" "PART" "QUIT"))
(erc-lurker-threshold-time (* 3600 4)) ; Four hours
(erc-prompt-for-nickerv-password nil)
(erc-server-reconnect-attempts 5)
(erc-server-reconnect-timeout 3)
:config
(add-to-list 'erc-modules 'spelling)
(erc-services-mode 1)
(erc-update-modules))
```

4.4.8 TODO Telegram

Yeah, a Telegram client exists for Emacs.

```
(use-package telega
  :load-path "~/telega.el/telega.el"
  :commands (telega)
  :defer t)
```

4.5 Coding languages

4.5.1 TODO Emacs Lisp

4.5.2 Python

Python is included by default on most Linux distributions.

```
(use-package py-yapf)
(add-hook 'python-mode-hook 'py-yapf-enable-on-save)
```

4.6 File formats

4.6.1 csv and Excel

```
(use-package csv-mode)
```

4.6.2 Interacting with PDFs

Org mode shines particularly when exporting to PDF — Org files can reliably be shared and exported to PDF in a reproducible fashion.

```
(use-package pdf-tools)
(pdf-tools-install)
```

4.6.3 Accounting

Ledger is a creation of John Wiegley's. It enables double-entry accounting in a simple plaintext format, and reliable verification of account balances through time.⁸

```
(use-package ledger-mode
  :bind
  ("C-c r" . ledger-report)
  ("C-c C" . ledger-mode-clean-buffer))
```

These reports can be generated within Emacs. It is quite useful to pipe their output to an automated “smart document”.

```
(setq ledger-reports
  '(("bal" "%(binary) -f %(ledger-file) bal")
    ("bal-USD" "%(binary) -f %(ledger-file) bal --exchange USD")
    ("reg" "%(binary) -f %(ledger-file) reg"))
```

⁸For more information, visit <https://www.ledger-cli.org/>.

```

("net-worth" "%(binary) -f %(ledger-file) bal ^Assets
  ↳ ^Liabilities --exchange USD")
("net-income" "%(binary) -f %(ledger-file) bal ^Income
  ↳ ^Expenses --exchange USD --depth 2 --invert")
("payee" "%(binary) -f %(ledger-file) reg @%(payee)")
("account" "%(binary) -f %(ledger-file) reg %(account)")
("budget" "%(binary) -f %(ledger-file) budget --exchange
  ↳ USD"))))

```

4.6.4 Plotting & charting

```
(use-package gnuplot)
```

4.7 Cosmetics

4.7.1 Start page

We replace the standard welcome screen with our own.

```

(setq inhibit-startup-message t)
(use-package dashboard
  :config
  (dashboard-setup-startup-hook)
  (setq dashboard-startup-banner (concat user-emacs-directory
    ↳ "img/icons/Safran_logo.svg"))
  (setq dashboard-items '((recents . 5)
                          (projects . 5)))
  (setq dashboard-banner-logo-title "A modern professional text
    ↳ editor."))

```

4.7.2 TODO Sidebar

Get inspiration from `ibuffer-sidebar` and create a better sidebar.

```

(defvar sd-sidebar nil "Becomes true if sd-sidebar is visible.")

(defun sd-sidebar (side)
  "Open the sidebar on the chosen SIDE of the buffer."
  (interactive)
  (cond ((eq sd-sidebar t)
    (unless (one-window-p)
      (delete-window)))

```

```
(setq sd-sidebar nil))
(string-equal side "left")
(split-window-right)
(dired ".")
(dired-hide-details-mode)
(setq sd-sidebar t))
(string-equal side "right")
(split-window-right)
(windmove-right)
(dired ".")
(dired-hide-details-mode)
(setq sd-sidebar t)))
```

4.7.3 Better parentheses

```
(use-package rainbow-delimiters
  :config (add-hook 'prog-mode-hook #'rainbow-delimiters-mode))
(show-paren-mode 1)
```

4.7.4 Highlight color keywords in that color

This highlights hexadecimal numbers which look like colors, in that same color.

```
(use-package rainbow-mode
  :init
  (add-hook 'prog-mode-hook 'rainbow-mode))
```

4.7.5 Minor modes in mode line

We hide minor modes in the mode line.

```
(use-package rich-minority)
(rich-minority-mode 1)
(setf rm-whitelist "projectile")
```

4.7.6 Emojis

Emojis are a symbol of modernity, and their tasteful use enables communicating with people from around the world — we're all for that! B-) 😊

```
(when (string-equal system-type "gnu/linux")
  (use-package emojiify
    :hook (after-init . global-emojiify-mode)))
```

5 org-mode

Org mode is so significant that this section of the paper deserves its own introduction.

5.1 Introduction

Phew, after all this initialization, I can finally introduce Org mode! I am so **excited**.

Org mode replaces a word processor, a presentation creator, and a spreadsheet editor. The spreadsheet ability captures more than 80% use cases wherein one wishes to include a table in a text document destined for physical publication. (It is clear that Excel spreadsheets are *not* destined for physical publication — simply attempt to print an Excel spreadsheet with the default settings.) In my opinion, Org mode matches all *useful* features of the Microsoft Office suite 1-to-1.

What follows are customizations designed to make Org mode behave more like Microsoft Word. The end goal is, once again, to draw as many new users to Emacs as possible!

Check out how much information Org mode keeps concerning the most recent header:

```
(save-excursion
  (org-previous-visible-heading 1)
  (org-entry-properties))

(This block was evaluated on Microsoft Windows.)

(("CATEGORY" . "smart-documents")
 ("BLOCKED" . "")
 ("FILE" . "c:/Users/blend/AppData/Roaming/.emacs.d/smart-documents.org")
 ("PRIORITY" . "A")
 ("ITEM" . "Introduction"))
```

5.2 Basic customization

5.2.1 Base folder

Org base directory is in user home on GNU/Linux, or in AppData in MS Windows.

```
(setq org-directory (concat user-emacs-directory "~/org"))
```

5.2.2 Prevent/warn on invisible edits

```
(setq org-catch-invisible-edits t)
```


5.3 Org cosmetics

First, we ensure the display of markup symbols for **bold**, *italic*, underlined and ~~strikethrough~~ text, and ensure our document appears indented upon loading.⁹

We then set values for many other Org-related cosmetic symbols.

```
(setq org-hide-emphasis-markers nil
      org-startup-indented t
      org-src-preserve-indentation nil
      org-edit-src-content-indentation 2
      org-ellipsis (propertyize " " ; folding symbol
                                'mouse-face 'highlight
                                'help-echo "Unfold section."))
```

5.3.1 Dynamic numbering of headlines

We enable the dynamic numbering of headlines in an Org buffer. We also set the numbering face to `org-special-keyword`, which specifies a `:background white` attribute. This is necessary because otherwise, the background of the numbering may be overridden by the `TODO` face attribute `:background coral`.

```
(add-hook 'org-mode-hook 'org-num-mode)
(setq org-num-face 'org-special-keyword)
```

By default, we hide Org document properties such as `#+TITLE`, `#+AUTHOR`, and `#+DATE`, because those keywords are defined when the document template is populated. We can nevertheless always access those properties and edit them manually, with a simple keyboard shortcut (cf. Section 3.2.9).

5.3.2 Document properties

```
(defun org-property-value (property)
  "Return the value of a given Org document property."
  (interactive)
  (save-excursion
    (goto-char (point-min))
    (re-search-forward
      (concat
        "^[:space:]]*#\\"
        property
```

⁹It *appears* indented, but the underlying plaintext file does not contain tab characters!

```

        ":[[:space:]]*\\(.*?\\)[[:space:]]*$")
      nil t)
(nth 3 (car (cdr (org-element-at-point))))))

(defun sd-document-properties ()
  "Open separate buffer to edit Org mode properties."
  (interactive)
  (let ((title (car (org-property-value "TITLE")))
        (date (org-property-value "DATE")))
    (with-output-to-temp-buffer "Smart Document Properties"
      (print title)
      (print date))))

(add-hook 'org-src-mode-hook
  '(lambda ()
     "Disable flycheck for `emacs-lisp-mode'."
     (setq-local flycheck-disabled-checkers
       '(emacs-lisp-checkdoc))))

```

5.3.3 Timestamps

More literary timestamps are exported to \LaTeX using the following custom format:

```

(setq org-time-stamp-custom-formats
  '("%d %b. %Y (%a)" . "%d %b. %Y (%a), at %H:%M"))

```

5.4 Programming a Smart Documents

The following languages can be used inside SRC blocks, in view of being executed by the Org Babel backend upon document export.

```

(setq org-babel-load-languages
  '((shell . t)
    (python . t)
    (plantuml . t)
    (emacs-lisp . t)
    (awk . t)
    (ledger . t)
    (gnuplot . t)
    (latex . t)))

(org-babel-do-load-languages

```

```
'org-babel-load-languages '((C . t)
                             (shell . t)
                             (gnuplot . t)))
```

5.5 Agenda

The agenda displays a chronological list of headings across all agenda files for which the heading or body contain a matching `org-time-stamp`.¹⁰

We open the agenda in a separate window.

```
(setq org-agenda-window-setup 'other-frame)
```

5.6 L^AT_EX export

We'll be compiling our documents with LuaTeX. This will afford us some future-proofing, since it was designated as the successor to pdfTeX by the latter's creators.

First, we define the command executed when an Org file is exported to L^AT_EX. We'll use `latexmk`, the Perl script which automagically runs binaries related to L^AT_EX in the correct order and the right amount of times.

Options and why we need them:

-shell-escape required by minted to color source blocks

-pdflatex=lualatex we use lualatex to generate our PDF

-interaction=nonstopmode go as far as possible without prompting user for input

```
(setq org-latex-pdf-process
      '("latexmk -pdf -f \
        -pdflatex=lualatex -shell-escape \
        -interaction=nonstopmode -outdir=%o %f"))
```

5.6.1 Exporting timestamps

We customize the format for org time stamps to make them appear monospaced in our exported L^AT_EX documents. This makes them visually distinguishable from body text.

```
(setq org-latex-active-timestamp-format
      "\\texttt{%s}")
(setq org-latex-inactive-timestamp-format
      "\\texttt{%s}")
```

¹⁰An `org-time-stamp` can be inserted with `C-c .` (period)

5.6.2 L^AT_EX packages

The following packages are loaded for every time we export to L^AT_EX.

```
(setq org-latex-packages-alist
  '(("AUTO" "babel" t
    ("pdflatex"))
    ("AUTO" "polyglossia" t ; Babel replacement for LuaLaTeX
    ("xelatex" "lualatex"))
    (" " "fontspec" t ; Fonts for LuaLaTeX
    ("lualatex"))
    (" " "booktabs" t ; Publication quality tables
    ("pdflatex" "lualatex"))
    (" " "wasysym" t ; Emojis and other symbols
    ("pdflatex" "lualatex"))
    (" " "lettrine" t
    ("pdflatex" "lualatex"))
    ("table,svgnames" "xcolor" t ; svgnames opens up ~150
    → new color keywords
    ("pdflatex" "lualatex"))
    ("skip=0.5\\baselineskip, width=0.618\\textwidth"
    → "caption" t ; Increase space between floats and
    → captions
    ("pdflatex" "lualatex"))))
```

5.6.3 Colored source blocks in PDF export

Little bonus for GNU/Linux users: syntax highlighting for source code blocks in L^AT_EX exports.

```
(when (string-equal system-type "gnu/linux")
  (add-to-list 'org-latex-packages-alist '("AUTO" "minted" t
    ("pdflatex"
    → "lualatex"))))

(setq org-latex-listings 'minted)
(setq org-latex-minted-options '(("style" "friendly")
  ("breaklines" "true")
  ("breakanywhere" "true"))))
```

5.6.4 Cleaning directory after export

Now, we set the files to be deleted when a \LaTeX \rightarrow PDF compilation occurs. We only care about two files, in the end: the Org mode file for edition, and the PDF for distribution.

```
(setq org-latex-logfiles-extensions
  '("aux" "bcf" "blg" "fdb_latexmk"
    "fls" "figlist" "idx" "log" "nav"
    "out" "ptc" "run.xml" "snm" "toc" "vrb" "xdv"
    "tex" "lot" "lof"))
```

5.6.5 Chronological diary entries

By default, Org agenda inserts diary entries as the first under the selected date. It is preferable to insert entries in the order that they were recorded, i.e. chronologically.

```
(setq org-agenda-insert-diary-strategy 'date-tree-last)
```

What follows is an additional document class structures that can be exported in \LaTeX .

```
;; (add-to-list 'org-latex-classes
;;             '("book-blendoit"
;;               "\\documentclass[12pt]{book}"
;;               ("\\chapter{%s}" . "\\chapter*{%s}")
;;               ("\\section{%s}" . "\\section*{%s}")
;;               ("\\subsection*{%s}" . "\\subsection*{%s}")
;;               ("\\subsubsection*{%s}" .
;;                 "\\subsubsection*{%s}"))
;;             ↪ "\\subsubsection*{%s}"))
```

5.6.6 Table of contents

By default, body text can immediately follow the table of contents. It is however cleaner to separate table of contents with the rest of the work.

```
(setq org-latex-toc-command "\\tableofcontents\\clearpage")
```

The following makes `TODO` items appear red and `CLOSED` items appear green in Org's \LaTeX exports. Very stylish, much flair!

5.7 TODO Org links

This is a mind-bending capacity of Org mode: we can assign arbitrary functions to be executed when a user follows an Org link. Org links appear like hyperlinks both in buffers and PDF exports — e.g. the following link to this very section, Section 5.7 — but their in-buffer behavior can be arbitrarily assigned.

```
(org-add-link-type
 "tag" 'endless/follow-tag-link)

(defun endless/follow-tag-link (tag)
  "Display a list of TODO headlines with tag TAG.
  With prefix argument, also display headlines without a TODO
  ↪ keyword."
  (org-tags-view (null current-prefix-arg) tag))

[[tag:work+phonenumber-boss][Optional Description]]
```

6 One-click workflows

In this section, we'll implement useful one-click workflows. It comes later keybinding definitions for two reasons:

1. To a new user, keybindings are more important than the precise implementation of the bound function — it is more important to know how to drive a car than how a car works.
2. If the following subsections share the same name as the keybinding subsection (Section 3), the links will resolve to the earliest heading in the document, i.e. the keybinding subsection and not the subsection describing the 'one-click workflow'.

6.1 TODO Export to PDF

This reimplements the most common Org mode export: Org → \LaTeX → PDF. The binding is defined in Section 3.8.1.

```
(defun sd-quick-export--org ()
  "Org mode async export to PDF and open.
  This basically reimplements `C-c C-e C-a l o'."
  (org-open-file (org-latex-export-to-pdf)))
```

```
(defun sd-quick-export--ledger-report ()
  "Quick export for `ledger-mode' report buffers."
  (let ((old-buffer (current-buffer)))
    (with-output-to-temp-buffer "**SD Export**"
      (print "#+SETUPFILE:
  ↪ ~/.emacs.d/templates/documents/default.org")
      (newline)
      (insert-buffer-substring old-buffer)
      (forward-line 10)
      (org-table-convert-region (point) (goto-char (point-max)))
      (setq more-lines-p t)
      (while more-lines-p
        (move-end-of-line 1)
        (newline)
        (setq more-lines-p (= 0 (forward-line 1))))
      (org-open-file (org-latex-export-to-pdf)))))

(defun sd-quick-export ()
  "Quickly prettify and export current buffer to PDF."
  (interactive)
  (cond ((eq major-mode 'org-mode)
        (sd-quick-export--org))
        ((eq major-mode 'emacs-lisp-mode)
        (message "No quick-export implemented yet.))
        ((eq major-mode 'ledger-report-mode)
        (sd-quick-export--ledger-report))
        (t (message (format "No sd-quick-export backend for %s."
                             major-mode)))))
```

6.2 Beautify buffer

Binding defined in Section 3.8.2.

```
(defun sd-indent-buffer ()
  "Indent entire buffer."
  (interactive)
  (save-excursion
    (indent-region (point-min) (point-max) nil)))

(defun sd-org-beautify ()
  "Beautify Org mode buffer."
```

```
(interactive)
(when (eq major-mode 'org-mode)
  (sd-indent-buffer))
```

7 Editing preferences

These customizations enhance editor usability. They also encompass cosmetic changes not brought about a specific package.

7.1 Editor

7.1.1 Coding standards

This is just a better default. Don't @ me.

```
(setq c-default-style "linux"
      c-basic-offset 4)
```

7.1.2 Recent files

The keybinding for opening a recently visited file is described in paragraph 3.2.5.

```
(recentf-mode 1)
(setq recentf-max-menu-items 25)
(setq recentf-max-saved-items 25)
(run-at-time nil (* 5 60) 'recentf-save-list)
```

7.2 Frame

7.2.1 Header & mode lines

1. **TODO** Icons We start by defining some icons we wish to include in our user interface. Emacs allows the usage of GIF images — this paves the way for UI elements which may be animated.

```
(defcustom sd-icon-loading
  (create-image
   (concat user-emacs-directory "img/icons/ellipsis.gif")
   'gif nil
   :scale 0.4)
  "The GIF representing \"loading\". Not animated by
  ↪ default."
```



```
:type 'sexp
:version "27.1"
:group 'sd)

(defun sd-icon-loading ()
  "Insert an animated blue ellipsis."
  (insert-image sd-icon-loading)
  (image-animate sd-icon-loading 0 t))
```

2. Header line

In Org mode, the document header line will be the title of the document we are working on currently. We start by defining keybindings for our header line buttons for navigating through open windows.

```
(defvar sd-header-line-previous-buffer-keymap
  ;; Add menu of window navigation to the header line.
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1] 'previous-buffer)
    map)
  "Keymap for what is displayed in the header line, with a
  ↪ single window.")

(defun sd-header-line-kill-buffer-keymap
  ;; Close current buffer and window.
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1]
      ↪ 'kill-buffer-and-window)
    map)
  "Keymap for closing current window.")

(defun sd-header-line-maximize-window-keymap
  ;; Maximize current window.
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1]
      ↪ 'delete-other-windows)
    map)
  "Keymap for maximizing the current window.")

(defun sd-header-line-minimize-window-keymap
  (let ((map (make-sparse-keymap)))
    (define-key map [header-line mouse-1] 'delete-window)
```

```
map)
"Keymap for minimizing the current window.")
```

Now, we describe the actual format of the header line.

```
(setq-default
 header-line-format
 '(:eval
  (list
   (if (eq (length (window-list)) 1)
       (propertyize " "
                    'face 'org-special-keyword
                    'mouse-face 'highlight
                    'keymap
                    ↪ sd-header-line-previous-buffer-keymap
                    'help-echo "Return to previous window.")
       (list (propertyize " "
                        'face 'org-special-keyword
                        'mouse-face 'org-todo
                        'keymap
                        ↪ sd-header-line-kill-buffer-keymap
                        'help-echo "Close this window.")
              (propertyize " "
                           'face 'org-special-keyword
                           'mouse-face 'highlight
                           'keymap sd-header-line-maximize-window
                           ↪ ow-keymap
                           'help-echo "Maximize this window.")
              (propertyize " "
                           'face 'org-special-keyword
                           'mouse-face 'highlight
                           'keymap sd-header-line-minimize-window
                           ↪ ow-keymap
                           'help-echo "Minimize this window.")))
   mode-line-buffer-identification)))

(image-animate sd-icon-loading 0 t)
```

3. Mode line

This interpretation of the ideal mode line is the result of carefully studying the default mode-line, as well as studying various customizations online.

```
(defvar sd-mode-line-lock-buffer-keymap
  ;; Lock buffer.
  (let ((map (make-sparse-keymap)))
    (define-key map [mode-line mouse-1] 'read-only-mode)
    map)
  "Keymap for locking/unlocking the current buffer.")

(setq-default
 mode-line-format
 (list
  mode-line-front-space
  '(:eval (if buffer-read-only
    (propertyize " "
      'keymap
      ↪ sd-mode-line-lock-buffer-keymap
      'help-echo "C-x C-q: unlock
      ↪ buffer.")
    (propertyize " "
      'keymap
      ↪ sd-mode-line-lock-buffer-keymap
      'help-echo "C-x C-q: lock buffer.")))
  '(:eval (if (buffer-modified-p)
    (propertyize " "
      'help-echo "Buffer is modified.")
    (propertyize " "
      'help-echo "Buffer is saved.")))
  mode-line-modes " "
  mode-line-end-spaces))
```

7.3 Window

7.4 Buffer

7.4.1 Save cursor location

Save cursor location in visited buffer after closing it or Emacs.

```
(save-place-mode 1)
```

7.4.2 Column filling

We leave the default `fill-column` unchanged, so as to minimally disrupt a user's existing documents.

```
(add-hook 'org-mode-hook
  'turn-on-auto-fill) ; Automatically break lines longer
                      ; than =fill-column=.
```

7.5 Text

7.5.1 Beautiful symbols

We want the Emacs Lisp keyword `lambda` to be rendered as λ within the editor. This is mostly for a subjective “cool” factor.

```
(global-prettify-symbols-mode 1)
```

7.5.2 Org mode sugar

Let's pimp out the appearance of our text in Org mode. First, we prettify checkbox lists.

```
(when (string-equal system-type "gnu/linux")
  (add-hook 'org-mode-hook
    (lambda ()
      "Beautify Org symbols."
      (push '("[ ]" . " ") prettify-symbols-alist) ;
        ↳ Unchecked item
      (push '("[X]" . " ") prettify-symbols-alist) ;
        ↳ Checked item
      (push '("[-]" . " ") prettify-symbols-alist) ;
        ↳ Partially checked item
      (push '("-" . " ") prettify-symbols-alist) ; DONE
        ↳ headings
      (prettify-symbols-mode))))
```

- ☐ This first item is unticked
- ☐ This second item is partially completed
 - ☒ This first sub-item is ticked
 - ☐ This sub-item is not ticked
- ☐ This third item is ticked

7.5.3 Electric modes

Electricity is a very important technology. In Emacs jargon, “electric” modes tend to automate behaviors or present some elegant simplification to a workflow.¹¹

```
(electric-pair-mode) ; Certain character pairs are automatically  
  ↪ completed.  
(electric-indent-mode) ; Newlines are always intelligently  
  ↪ indented.
```

7.6 Minibuffer

We replace the longer yes-or-no-p questions with more convenient y-or-n-p.

```
(defalias 'yes-or-no-p 'y-or-n-p)
```

Disable minibuffer scroll bar.

```
(set-window-scroll-bars (minibuffer-window) nil nil)
```

8 Themes

Without a carefully designed theme, our editor would become unusable. Thus, we describe two themes that were developed purposefully and iteratively.

```
(setq custom-theme-directory (concat user-emacs-directory  
  ↪ "themes/"))  
;; (load-theme 'sd-light)  
(load-theme 'sd-dark)
```

8.1 My light and dark themes

A highly legible, unambiguous, and classic theme.

8.1.1 Colors

The default face is a black foreground on a white background, this matches MS Word. We are striving for a simple, intuitive color scheme.

Most of the visual cues derived from color are identical in both light and dark themes (Table 2).

¹¹More information can be found at <https://www.emacswiki.org/emacs/Electricity>.

Table 2: Light and dark themes' colors.

Color	blendoit-light	blendoit-dark
Black	default text	default background
Lighter shades	lesser headers	<i>n/a</i>
White	default background	default text
Darker shades	<i>n/a</i>	lesser headers
Red	negative	<i>same</i>
Tomato	timestamp 'TODO'	<i>same</i>
Green	positive	<i>same</i>
ForestGreen	timestamp 'DONE'	<i>same</i>
Blue	interactive content; links	<i>same</i>
SteelBlue	anything Org mode; anchor color	<i>same</i>
DeepSkyBlue	highlight	<i>same</i>
DodgerBlue	isearch	<i>same</i>
Purple	Code syntax highlighting	<i>same</i>

8.1.2 Cursors

In order to imitate other modern text editors, we resort to a blinking bar cursor. We choose red, the most captivating color, because the cursor is arguably the region on our screen:

1. most often looked at;
2. most often searched when lost.

In files containing only *fixed-pitch* fonts (i.e. files containing only code), the cursor becomes a high-visibility box.

In files containing a mix of *variable-pitch* and *fixed-pitch* fonts, the cursor is a more MS Word-like bar.

```
(setq-default cursor-type 'bar)
```

8.1.3 Fonts

1. Currently used *chad* fonts

Hack¹² default and fixed-pitch, default code font

- Legible, modern monospace font
- Strict, sharp, uncompromising

Public Sans¹³ variable-pitch, default body text font

- Very modern yet neutral
- Designed for the U.S. government
- Exceptional color on screen

Hermit¹⁴ org-block, anything Org/meta in general

- Slightly wider than Hack
- More opinionated shapes
- Very legible parentheses, very useful for Emacs Lisp!

Courier Prime¹⁵ :: certain monospace usages

Jost¹⁶ org-document-title and org-level-1

¹²<https://sourcefoundry.org/hack/>

¹³<https://public-sans.digital.gov/>

¹⁴<https://pcaro.es/p/hermit/>

¹⁵<https://quoteunquoteapps.com/courierprime/index.php>

¹⁶<https://indestructibletype.com/Jost.html>

- Ultra-modern
- Tasteful amount of geometric inspiration

2. Previously used *virgin* fonts

Liberation Sans¹⁷ ~~variable-pitch~~

- Metrically compatible with *Arial* (ugh)
- Unoffensive, unambitious forms
- Pretty angular letters, it's like you're trying to read squares

Open Sans¹⁸ ~~variable-pitch~~

- Ooh geometric Bauhaus influences, look at me
- Tall leading height is *h a r m o n i o u s*

3. Using proportional fonts when needed

We use `variable-pitch-mode` for appropriate modes.

```
(add-hook 'org-mode-hook 'variable-pitch-mode)
(add-hook 'info-mode-hook 'variable-pitch-mode)
```

4. **TODO** Default font size

Make default font size larger on displays of which the resolution is greater than 1920×1080.

```
(if (< screen-width 1920)
    (default-font)
    else)
```

8.2 **TODO** Wealthy theme

GOOD golly, nobody wishes for a *pedestrian* theme! Let your entourage know that you're rocking an editor fit for a king with this finely crafted 'wealthy' theme. Selecting it shall enable the following fancitudes:

1. The default font shall be sublimed in the form of *EB Garamond*
2. Bullets will be tastefully replaced with pointing fingers
3. Heading stars will be replaced with Black Queen chess pieces

¹⁷https://en.wikipedia.org/wiki/Liberation_fonts

¹⁸<https://www.opensans.com/>



Figure 1: Claude Garamont, an icon of font design. World-renowned for his elegant typefaces, which inspired many generations of typographers.

CLAUDE Garamont (c. 1510--1561), known commonly as **Claude Garamond**, was a French type designer, publisher and punch-cutter based in Paris. Garamond worked as an engraver of punches, the masters used to stamp matrices, the moulds used to cast metal type. He worked in the tradition now called old-style serif design, which produced letters with a relatively organic structure resembling handwriting with a pen but with a slightly more structured and upright design. Considered one of the leading type designers of all time, he is recognised to this day for the elegance of his typefaces. Many old-style serif typefaces are collectively known as Garamond, named after the designer.

From https://en.wikipedia.org/wiki/Claude_Garamond

8.2.1 Symbol substitution

```
(defun sd-wealthy ()  
  "Beautify symbols for our wealthy theme."  
  (push '("-" . " ") prettify-symbols-alist) ; unnumbered  
    ↪ bullets  
  (push '("*" . " ") prettify-symbols-alist) ; headings  
  (prettify-symbols-mode))
```

8.3 TODO minimal

9 Late setup

At this point, our editor is almost ready to run. Phew! All that's left to do is to interrupt our profiling activities, and smartly store the result of our profiling.

9.1 Profiling — stop

```
;; (profiler-stop)
```

9.2 Profiling — report

```
;; (profiler-report)
```

10 Conclusion

In this configuration file, we described a series of customization steps taken to make Emacs more palatable to modern word processors users.

We will now go through the appendices in the following order:

1. Ideas implemented, then retired;
2. Risky ideas that might displease Emacs when it reads our literate configuration. If these risky ideas are included in the main body of the paper, it becomes difficult to identify which one is causing trouble.

A Unpacking our literate configuration

The following code blocks are normally evaluated once---upon starting Emacs for the first time.

```
(defvar sd-packed-p t
  "Boolean to track literate configuration packed/unpacked
  ↪ status.")

(defvar sd-unpack-sections (org-property-values "sd-unpack-path")
  "List of target sections in `my/literate-config' to be
  ↪ unpacked.")
```

```
(defun sd-unpack-sections ()
  "Unpack literate configuration into `emacs-user-directory'."
  (interactive)
  (mapcar 'sd-unpack sd-unpack-sections)
)

(defun sd-unpack-section (&optional section)
  "Unpack SECTION into `user-emacs-directory'.
   If nil, unpack section under point.
   Make go through list of headings and unpack first matching
   ↪ SECTION."
  (interactive)
  (if (not section)
      (insert
       (concat
        "\n\nThe contents of this Section was automatically moved
        ↪ to\n\n"
        user-emacs-directory (org-entry-get nil
        ↪ "sd-unpack-path") "=\n\n"
        "Use `sd-pack-section' to copy the contents back into
        ↪ this section."))))))

(defun sd-pack-section ()
  "Pack SECTION into `my/literate-config'."
  (interactive)
  (message "foobar!!!"))

(global-set-key (kbd "C-t") 'sd-pack-section)

(sd-unpack "init.el")
```